


# CITY OF ROLLING HILLS ESTATES CALIFORNIA CONSTRUCTION PLANS

## FOR INTERSECTION CAPACITY IMPROVEMENTS AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE FY 2020-2021



VICINITY MAP  
N.T.S.

### SHEET INDEX

SHEET NO.	DESCRIPTION
SHEET NO. 1	TITLE SHEET
SHEET NO. 2	TYPICAL SECTIONS AND DETAIL
SHEET NO. 3	STREET IMPROVEMENT PLAN AND PROFILE
SHEET NO. 4	STREET IMPROVEMENT PLAN AND PROFILE
SHEET NO. 5	STREET IMPROVEMENT PLAN AND PROFILE
SHEET NO. 6	RETAINING WALL PLAN AND PROFILE
SHEET NO. 7	RETAINING WALL PLAN AND PROFILE
SHEET NO. 8	RETAINING WALL PLAN AND PROFILE
SHEET NO. 9	RETAINING WALL PLAN AND PROFILE
SHEET NO. 10	RETAINING WALL PLAN AND PROFILE
SHEET NO. 11	TRAFFIC SIGNAL MODIFICATION PLAN
SHEET NO. 12	TRAFFIC SIGNAL DECORATIVE POLE DETAILS
SHEET NO. 13	TRAFFIC SIGNAL FOUNDATION DETAILS
SHEET NO. 14	SIGNING AND STRIPING PLAN
SHEET NO. 15	STREET MEDIAN & PARKWAY LANDSCAPE CONSTRUCTION PLAN
SHEET NO. 16	STREET MEDIAN & PARKWAY IRRIGATION PLAN
SHEET NO. 17	STREET MEDIAN & PARKWAY IRRIGATION LEGEND & NOTES
SHEET NO. 18	STREET MEDIAN & PARKWAY PLANTING PLAN
SHEET NO. 19	BUS SHELTER DETAILS
SHEET NO. 20	BUS SHELTER LAYOUT AND CONSTRUCTION NOTES
SHEET NO. 21	IRRIGATION DETAILS
SHEET NO. 22	LANDSCAPE CONSTRUCTION DETAILS

### UTILITY CONTACT

CALIFORNIA WATER SERVICE CO.  
ATTN: BRETT OMMEN, DISTRICT SUPERINTENDENT (310)377-5528  
PLANNER: CARDINAL FERNANDEZES  
(310)377-5528  
EMAIL: CFERNANDEZES@CALWATER.COM

COUNTY SANITATION DISTRICT OF LOS ANGELES COUNTY  
ATTN: DOUG WALTON (310)638-1161

COX COMMUNICATIONS  
ATTN: SUSAN SCHUTZMAN (619)266-5605  
EMAIL: SUSAN.SCHUTZMAN@COX.COM


LOS ANGELES COUNTY DEPARTMENT OF PUBLIC WORKS  
ATTN: DARYLL CHENOWETH  
(626)459-9109  
EMAIL: DCHENOWETH@DPW.LACOUNTY.COV

SOUTHERN CALIFORNIA EDISON  
ATTN: TAYLOR RUIZE/LOCAL PLANNER  
(310)783-9426  
EMAIL: FRANCISCO.M.MARTINEZ@SCE.COM

THE GAS COMPANY  
ATTN: FAVIOLA OCHOA  
(213)808-7857  
EMAIL: FAVIOCHOA@SEMPRAUTILITES.COM

### GENERAL CONSTRUCTION NOTES:

- ALL WORK SHOWN HEREON SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION, CURRENT EDITION.
- THE CONTRACTOR IS REQUIRED TO TAKE DUE PRECAUTIONARY MEASURES TO PROTECT THE UTILITIES OR SUBSTRUCTURES FOUND AT THE SITE. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO NOTIFY THE OWNERS OF THE UTILITIES OR SUBSTRUCTURES CONCERNED BEFORE STARTING WORK (72-HOURS NOTICE REQUIRED.) PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL CONTACT UNDERGROUND SERVICE ALERT (USA) TOLL FREE AT 1-800-227-2600.
- PRIOR TO BEGINNING OF CONSTRUCTION, THE CONTRACTOR SHALL SUBMIT A TRAFFIC CONTROL PLAN FOR DISRUPTIVE STREET WORK, INCLUDING CONSTRUCTION SCHEDULE - SUBJECT TO APPROVAL BY THE ENGINEER. MINIMUM REQUIREMENTS ARE STATED IN THE SPECIFICATIONS. CONSTRUCTION WARNING DEVICES, SIGNS, ETC., SHALL CONFORM WITH CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.
- CONTRACTOR SHALL PROTECT ALL EXISTING PROPERTIES FROM DAMAGE IN ACCORDANCE WITH PROJECT SPECIFICATIONS




### CONSTRUCTION NOTES

- REMOVE EXISTING ASPHALT CONCRETE, P.C.C., BASE MATERIAL, AND SUBGRADE
  - CONSTRUCT 6-INCH THICK AC OVER 10-INCH THICK CAB, SEE TYPICAL SECTION ON SHEET 2.
  - COLDMILL EXISTING AC PAVEMENT 2-INCH DEPTH
  - CONSTRUCT 2-INCH THICK ASPHALT RUBBER HOT MIX (ARHM) OVERLAY.
  - CONSTRUCT ROLLED CURB TYPE R-2 PER DETAIL A ON SHEET 2.
  - CONSTRUCT ROLLED CURB TRANSITION PER DETAIL ON SHEET 2.
  - CONSTRUCT CURB AND GUTTER PER SPPCW STD PLAN 120-3, TYPE A2-6
  - CONSTRUCT CURB PER SPPCW STD PLAN NO. 120-3, TYPE A1-6
  - CONSTRUCT 4-INCH AC OVER 4-INCH AB MULTI-USE PATH
  - CONSTRUCT CURB RAMP PER SPPCW STD PLAN 111-5, CASE AND TYPE PER PLAN
  - CONSTRUCT CROSS AND LONGITUDINAL GUTTER PER SPPCW STD PLAN NO. 122-3
  - CONSTRUCT 4-INCH THICK P.C.C. RESIDENTIAL DRIVEWAY PER SPPCW STD PLAN NO. 110-2
  - CONSTRUCT 4-INCH THICK PCC SIDEWALK PER SPPCW STD PLAN NO. 110-2, OVER 6-INCH CAB
  - CONSTRUCT CURB AND GUTTER PER SPPCW STD PLAN 120-3, TYPE A2-6, W=1'
  - CONSTRUCT RETAINING WALL PER DETAIL B ON SHEET 9
  - CONSTRUCT CONCRETE DRAINAGE SWALE BEHIND RETAINING WALL PER SPPCW STD PLAN NO. 621-3
  - CONSTRUCT RETAINING WALL, TYPE 7A, PER SPPCW STD PLAN NO. 616-3
  - CONSTRUCT RETAINING WALL, TYPE 5, PER SPPCW STD PLAN NO. 614-3. CASE PER PLAN
  - CONSTRUCT RETAINING WALL, TYPE 5, MODIFIED PER DETAIL HEREON SPPCW STD PLAN NO. 614-3. CASE PER PLAN
  - CONSTRUCT 1-INCH THICK PCC BUS PAD INCLUDING 6-INCH MONOLITHIC CURB, 3,250 PSI OVER 6-INCH CAB
  - COMPACTED NATIVE BACKFILL AT 90% RELATIVE COMPACTION TO A DEPTH OF 12"
  - CONSTRUCT WALL GUTTER OUTLET TO FACE OF WALL PER SPPCW STD PLAN NO. 617-3
  - CONSTRUCT WALL GUTTER OUTLET TO CURB PER SPPCW STD PLAN NO. 617-3 AND PLAN No. 150-4
  - CONSTRUCT CABLE RAILING PER CALTRANS STD B11-47, PER SECTION C-C
- (P) PROTECT IN PLACE.  
(RL) RELOCATE TYPE AS SHOWN.  
(R) RELOCATE BY OTHERS.  
(R) REMOVE TYPE AS SHOWN.  
(AG) ADJUST TO GRADE TYPE AS SHOWN.  
(AO) ADJUST TO GRADE BY OTHERS.  
(LS) SEE LANDSCAPE PLANS  
(SS) SEE SIGNING AND STRIPING PLANS.  
(TS) SEE TRAFFIC SIGNAL PLANS.  
(MFL) INDICATES MEDIAN FLARE PER SPPCW STD PLAN NO. 141-2

### ABBREVIATIONS

AB	AGGREGATE BASE
AC	ASPHALT CONCRETE
AP	ANGLE POINT
AV	AIR VAC
BC	BEGIN CURVE
BCR	BEGIN CURB RETURN
BEG	BEGIN
BO	BLOWOFF
BVC	BEGIN VERTICAL CURVE
BW	BACK OF WALK
BX	BOTTOM OF X
C&G	CURB AND GUTTER
CAB	CRUSHED AGGREGATE BASE
CB	CATCH BASIN
C/CL	CENTERLINE
CF	CURB FACE
CLF	COLD IN-PLACE RECYCLE CHAIN LINK FENCE
CLR	CLEAR
CONC	CONCRETE
CONC.	CONSTRUCTION
CPC	CALIFORNIA PLUMBING CODE
DI	DUCTILE IRON
DWY	DRIVEWAY
DWG	DRAWING
E	EAST
EC	END CURVE
ECR	END CURB RETURN
EG	EDGE OF GUTTER
E.J.	EXPANSION JOINT
ELEV	ELEVATION
EP	EDGE OF PAVEMENT
EVC	END VERTICAL CURVE
EX/EXIST	EXISTING
FDR	FULL DEPTH RECLAMATION
FG	FINISHED GRADE
FH	FIRE HYDRANT
FL	FLOWLINE
FS	FINISHED SURFACE
GB	GRADE BREAK
GI	GALVANIZED IRON
GL	GUTTER LIP
HMA	HOT MIX ASPHALT
HP	HINGE POINT
HTF	HIGH TENSILE FIBER
INT.	INTERSECTION
INV	INVERT
L	LENGTH
LF	LINEAR FEET
LIP	LIP OF GUTTER
LOL	LAYOUT LINE
LT	LEFT, LIGHT
MAX	MAXIMUM
MH	MANHOLE
MIN	MINIMUM
N	NORTH
N.I.C.	NOT IN CONTRACT
NLY	NORTHERLY
NO	NUMBER
NTS	NOT TO SCALE
O.C.	ON CENTER
OG	ORIGINAL GROUND
OH	OVERHEAD
PI	POINT OF INTERSECTION
PCC	PORTLAND CEMENT CONCRETE
PG	PROFILE GRADE
PG&E	PACIFIC GAS AND ELECTRIC
PMB	PROCESSED MISCELLANEOUS BASE
P.O.C.	POINT OF CONNECTION
PP	POWER POLE
PRC	POINT OF REVERSE CURVE
PROP.	PROPOSED
PRVC	POINT OF REVERSE VERTICAL CURVE
PT.	POINT
PVC	POLYVINYL CHLORIDE
PVMT.	PAVEMENT
R	RATE, RADIUS
R.C.	RELATIVE COMPACTION
RCP	REINFORCED CONCRETE PIPE
REQ'D	REQUIRED
RSP	ROCK SLOPE PROTECTION
RT	RIGHT
R/W	RIGHT-OF-WAY
S	SLOPE
S'LY	SOUTHERLY
SCE	SOUTHERN CALIFORNIA EDISON
SCH	SCHEDULE
SDMH	STORM DRAIN MANHOLE
SDWK	SIDEWALK
ST	STREET
STA	STATION
STD	STANDARD
ST.GR.	STRAIGHT GRADE
TC	TOP OF CURB
TELE	TELEPHONE
TG	TOP OF GRATE
TOP	TOP OF PLATFORM
TR	TOP OF RAIL
TW	TOP OF WALL
TX	TOP OF X
TYP	TYPICAL
V	DEPTH
VARIES	VARIABLE
VCP	VITRIFIED CLAY PIPE
W	WIDTH, WEST
WM	WATER METER
WV	WATER VALVE

U:\110176 - RHE PVDN@DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\PL-TITLE-01.dwg Apr 05, 23 - 10:03am



PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
13191 CROSSROADS PARKWAY NORTH  
SUITE 405 INDUSTRY, CA 91746-3497  
(562) 908-6200  
UNDER THE SUPERVISION OF  
TYRONE PETER RCE No. 81888 DATE

BENCH MARK:		REVISIONS	
NO.	DESCRIPTION	NO.	DATE
NO. _____	ELEV. _____		
DATE ADJ. _____	QUAD. _____		
NONE			


**CITY OF ROLLING HILLS ESTATES**

**TITLE SHEET**

**INTERSECTION CAPACITY IMPROVEMENTS  
AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE**

DRAWN BY: BR	SHT. 1 OF 22 SHTS.
DESIGNED BY: BR	
CHECKED BY: FW	


100% SUBMITTAL NOT FOR CONSTRUCTION




TYPICAL STREET SECTION FOR PALOS VERDES DRIVE NORTH  
N.T.S.

**CONSTRUCTION NOTES:**


- ① REMOVE EXISTING ASPHALT CONCRETE, P.C.C., BASE MATERIAL, AND SUBGRADE
- ② CONSTRUCT 6-INCH THICK AC OVER 10-INCH THICK CAB, SEE TYPICAL SECTION ON SHEET 2.
- ③ COLDMILL EXISTING AC PAVEMENT 2-INCH DEPTH
- ④ CONSTRUCT 2-INCH THICK ASPHALT RUBBER HOT MIX (ARHM) OVERLAY.
- ⑤ CONSTRUCT ROLLED CURB TYPE R-2 PER DETAIL A ON SHEET 2.
- ⑥ CONSTRUCT ROLLED CURB TRANSITION PER DETAIL ON SHEET 2.
- ⑦ CONSTRUCT CURB AND GUTTER PER SPPCW STD PLAN 120-3, TYPE A2-6
- ⑧ CONSTRUCT CURB PER SPPWC STD PLAN NO. 120-3, TYPE A1-6
- ⑨ CONSTRUCT 4-INCH AC OVER 4-INCH AB MULTI-USE PATH




TYPICAL STREET SECTION FOR PALOS VERDES DRIVE NORTH  
N.T.S.



ROLLED CURB TRANSITION DETAIL  
NTS




TYPE R-2  
ROLLED CURB DETAIL "A"  
NTS



TYPICAL STREET SECTION FOR PALOS VERDES DRIVE NORTH  
N.T.S.

U:\110176 - RHE PVDN@DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\PL-SECT&DET.dwg Apr 05, 23 - 10:04am

100% SUBMITTAL NOT FOR CONSTRUCTION



PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
13191 CROSSROADS PARKWAY NORTH  
SUITE 405 INDUSTRY, CA 91746-3497  
(562) 908-6200  
UNDER THE SUPERVISION OF  
TYRONE PETER RCE No. 81888 DATE

BENCH MARK:  
NO. \_\_\_\_\_ ELEV. \_\_\_\_\_  
DATE ADJ. \_\_\_\_\_ QUAD. \_\_\_\_\_  
NONE


REVISIONS		
NO.	DESCRIPTION	APP. DATE

**CITY OF ROLLING HILLS ESTATES**

**TYPICAL SECTIONS AND DETAIL**

INTERSECTION CAPACITY IMPROVEMENTS  
AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

DRAWN BY: BR	SHT. 2 OF 22 SHTS.
DESIGNED BY: BR	
CHECKED BY: FW	




PROFILE SCALE  
HORIZ.: 1" = 20'  
VERT.: 1" = 4'

**CONSTRUCTION NOTES:**

- ① REMOVE EXISTING ASPHALT CONCRETE, P.C.C., BASE MATERIAL, AND SUBGRADE
- ② CONSTRUCT 6-INCH THICK AC OVER 10-INCH THICK CAB, SEE TYPICAL SECTION ON SHEET 2.
- ③ COLDMILL EXISTING AC PAVEMENT 2-INCH DEPTH
- ④ CONSTRUCT 2-INCH THICK ASPHALT RUBBER HOT MIX (ARHM) OVERLAY.
- ⑤ CONSTRUCT ROLLED CURB TYPE R-2 PER DETAIL A ON SHEET 2.
- ⑥ CONSTRUCT ROLLED CURB TRANSITION PER DETAIL ON SHEET 2.
- ⑦ CONSTRUCT CURB AND GUTTER PER SPPWC STD PLAN 120-3, TYPE A2-6
- ⑧ CONSTRUCT CURB PER SPPWC STD PLAN NO. 120-3, TYPE A1-6
- ⑨ CONSTRUCT 4-INCH AC OVER 4-INCH AB MULTI-USE PATH


- Ⓟ PROTECT IN PLACE.
- Ⓡ RELOCATE TYPE AS SHOWN.
- Ⓡ RELOCATE BY OTHERS.
- Ⓡ REMOVE TYPE AS SHOWN.
- Ⓐ ADJUST TO GRADE TYPE AS SHOWN.
- Ⓐ ADJUST TO GRADE BY OTHERS.
- Ⓛ SEE LANDSCAPE PLANS
- Ⓢ SEE SIGNING AND STRIPING PLANS.
- Ⓢ SEE TRAFFIC SIGNAL PLANS.
- Ⓜ INDICATES MEDIAN FLARE PER SPPWC STD PLAN NO. 141-2



**LEGEND**

	PROPOSED AC PAVEMENT AND OVERLAY
	PROPOSED PCC
	PROPOSED COLD MILL AND OVERLAY
	PROPOSED AC

- NOTE:**
1. SEE LANDSCAPE PLANS FOR VINYL RAIL FENCE INSTALLATION AND TREE REMOVAL LOCATIONS
  2. FOR CURVE DATA TABLE SEE SHEET 5
  3. FOR RETAINING WALLS SEE RETAINING WALL PLAN AND PROFILE



PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
13191 CROSSROADS PARKWAY NORTH  
SUITE 405 INDUSTRY, CA 91746-3497  
(562) 908-6200  
UNDER THE SUPERVISION OF  
TYRONE PETER RCE No. 81888 DATE

BENCH MARK:  
NO. \_\_\_\_\_ ELEV. \_\_\_\_\_  
DATE ADJ. \_\_\_\_\_ QUAD. \_\_\_\_\_  
NONE

REVISIONS		
NO.	DESCRIPTION	APP. DATE

**CITY OF ROLLING HILLS ESTATES**

**STREET IMPROVEMENT PLAN AND PROFILE**


INTERSECTION CAPACITY IMPROVEMENTS  
AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

DRAWN BY: BR  
DESIGNED BY: BR  
CHECKED BY: FW


SHT. 3 OF 22 SHTS.

U:\110176 - RHE PVDN\DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\PL-ROAD-01.dwg Apr 05 23 - 10:17am

100% SUBMITTAL NOT FOR CONSTRUCTION




PROFILE SCALE  
HORIZ.: 1" = 20'  
VERT.: 1" = 4'




- CONSTRUCTION NOTES:**
- REMOVE EXISTING ASPHALT CONCRETE, P.C.C., BASE MATERIAL, AND SUBGRADE
  - CONSTRUCT 6-INCH THICK AC OVER 10-INCH THICK CAB, SEE TYPICAL SECTION ON SHEET 2.
  - COLDMILL EXISTING AC PAVEMENT 2-INCH DEPTH
  - CONSTRUCT 2-INCH THICK ASPHALT RUBBER HOT MIX (ARHM) OVERLAY.
  - CONSTRUCT ROLLED CURB TYPE R-2 PER DETAIL A ON SHEET 2.
  - CONSTRUCT ROLLED CURB TRANSITION PER DETAIL ON SHEET 2.
  - CONSTRUCT CURB AND GUTTER PER SPPCW STD PLAN 120-3, TYPE A2-6
  - CONSTRUCT CURB PER SPPWC STD PLAN NO. 120-3, TYPE A1-6
  - CONSTRUCT 4-INCH AC OVER 4-INCH AB MULTI-USE PATH
  - CONSTRUCT CURB RAMP PER SPPWC STD PLAN 111-5, CASE AND TYPE PER PLAN
  - CONSTRUCT CROSS AND LONGITUDINAL GUTTER PER SPPWC STD PLAN NO. 122-3
  - CONSTRUCT 4-INCH THICK P.C.C. RESIDENTIAL DRIVEWAY PER SPPWC STD PLAN NO. 110-2
  - CONSTRUCT 4-INCH THICK PCC SIDEWALK PER SPPWC STD PLAN NO. 110-2, OVER 6-INCH CAB
  - CONSTRUCT CURB AND GUTTER PER SPPCW STD PLAN 120-3, TYPE A2-6, W=1'
  - CONSTRUCT RETAINING WALL, TYPE 7A, PER SPPWC STD PLAN NO. 616-3
  - CONSTRUCT 1-INCH THICK PCC BUS PAD INCLUDING 6-INCH MONOLITHIC CURB, 3,250 PSI OVER 6-INCH CAB
  - COMPACTED NATIVE BACKFILL AT 90% RELATIVE COMPACTION TO A DEPTH OF 12"

- (P) PROTECT IN PLACE.
- (RL) RELOCATE TYPE AS SHOWN.
- (R) RELOCATE BY OTHERS.
- (R) REMOVE TYPE AS SHOWN.
- (AG) ADJUST TO GRADE TYPE AS SHOWN.
- (AO) ADJUST TO GRADE BY OTHERS.
- (LS) SEE LANDSCAPE PLANS
- (SS) SEE SIGNING AND STRIPING PLANS.
- (TS) SEE TRAFFIC SIGNAL PLANS.
- (MF) INDICATES MEDIAN FLARE PER SPPWC STD PLAN NO. 141-2



- LEGEND**
- PROPOSED AC PAVEMENT AND OVERLAY
  - PROPOSED PCC
  - PROPOSED COLD MILL AND OVERLAY
  - PROPOSED AC



PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
13191 CROSSROADS PARKWAY NORTH  
SUITE 405 INDUSTRY, CA 91746-3497  
(562) 908-6200  
UNDER THE SUPERVISION OF  
TYRONE PETER RCE No. 81888 DATE

BENCH MARK:  
NO. \_\_\_\_\_ ELEV. \_\_\_\_\_  
DATE ADJ. \_\_\_\_\_ QUAD. \_\_\_\_\_  
NONE

REVISIONS		
NO.	DESCRIPTION	APP. DATE

**CITY OF ROLLING HILLS ESTATES**

**STREET IMPROVEMENT PLAN AND PROFILE**


INTERSECTION CAPACITY IMPROVEMENTS  
AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

DRAWN BY: BR  
DESIGNED BY: BR  
CHECKED BY: FW


SHT. 4 OF 22 SHTS.

U:\110176 - RHE PVD\DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\PL-ROAD-01.dwg Apr 05, 23 - 10:18am

100% SUBMITTAL NOT FOR CONSTRUCTION




PROFILE SCALE  
HORIZ.: 1" = 20'  
VERT.: 1" = 4'



CURVE DATA				
CURVE	LENGTH	RADIUS	DELTA	TANGENT
1	31.314'	92.50'	19°23'47"	15.81'
2	31.314'	92.50'	19°23'47"	15.81'
3	42.459'	28.00'	86°53'01"	26.52'
4	14.624'	10.00'	83°47'18"	8.97'
5	16.759'	13.00'	73°51'41"	9.77'
6	19.191'	62.00'	17°44'07"	9.67'
7	15.477'	50.00'	17°44'07"	7.80'
8	14.314'	55.00'	14°54'42"	7.20'
9	19.615'	80.00'	14°02'53"	9.86'
10	9.247'	45.00'	11°46'24"	4.64'
11	37.744'	109.00'	19°50'24"	19.06'
12	1.235'	5.00'	14°09'15"	0.62'
13	31.314'	92.50'	19°23'47"	15.81'
14	31.314'	92.50'	19°23'47"	15.81'
15	30.626'	87.19'	20°07'33"	15.47'
16	30.626'	87.19'	20°07'33"	15.47'
17	199.408'	893.50'	12°47'13"	100.12'
18	330.692'	935.00'	20°15'52"	167.09'
19	87.051'	40.00'	124°41'27"	76.34'
20	218.811'	966.00'	12°58'42"	109.88'
21	11.276'	31.25'	20°40'26"	5.70'
22	34.380'	154.35'	12°45'44"	17.26'
23	47.235'	120.00'	22°33'11"	23.93'
24	248.679'	966.00'	14°44'59"	125.03'
25	12.568'	100.00'	7°12'03"	6.29'
26	31.899'	150.00'	12°11'04"	16.01'
27	42.564'	131.50'	18°32'43"	21.47'
28	22.565'	130.00'	9°56'43"	11.31'
29	675.200'	1000.00'	38°41'10"	351.04'


- CONSTRUCTION NOTES:**
- REMOVE EXISTING ASPHALT CONCRETE, P.C.C., BASE MATERIAL, AND SUBGRADE
  - CONSTRUCT 6-INCH THICK AC OVER 10-INCH THICK CAB, SEE TYPICAL SECTION ON SHEET 2.
  - COLDMILL EXISTING AC PAVEMENT 2-INCH DEPTH
  - CONSTRUCT 2-INCH THICK ASPHALT RUBBER HOT MIX (ARHM) OVERLAY.
  - CONSTRUCT ROLLED CURB TYPE R-2 PER DETAIL A ON SHEET 2.
  - CONSTRUCT ROLLED CURB TRANSITION PER DETAIL ON SHEET 2.
  - CONSTRUCT CURB AND GUTTER PER SPPWC STD PLAN 120-3, TYPE A2-6
  - CONSTRUCT CURB PER SPPWC STD PLAN NO. 120-3, TYPE A1-6
  - CONSTRUCT 4-INCH AC OVER 4-INCH AB MULTI-USE PATH
  - CONSTRUCT CURB RAMP PER SPPWC STD PLAN 111-5, CASE AND TYPE PER PLAN
  - CONSTRUCT CROSS AND LONGITUDINAL GUTTER PER SPPWC STD PLAN NO. 122-3
  - CONSTRUCT 4-INCH THICK P.C.C. RESIDENTIAL DRIVEWAY PER SPPWC STD PLAN NO. 110-2
  - CONSTRUCT 4-INCH THICK PCC SIDEWALK PER SPPWC STD PLAN NO. 110-2, OVER 6-INCH CAB
  - CONSTRUCT CURB AND GUTTER PER SPPWC STD PLAN 120-3, TYPE A2-6, W=1'

- (P) PROTECT IN PLACE.
- (RL) RELOCATE TYPE AS SHOWN.
- (RO) RELOCATE BY OTHERS.
- (R) REMOVE TYPE AS SHOWN.
- (AG) ADJUST TO GRADE TYPE AS SHOWN.
- (AO) ADJUST TO GRADE BY OTHERS.
- (LS) SEE LANDSCAPE PLANS
- (SS) SEE SIGNING AND STRIPING PLANS.
- (TS) SEE TRAFFIC SIGNAL PLANS.
- (MFL) INDICATES MEDIAN FLARE PER SPPWC STD PLAN NO. 141-2



- LEGEND**
- PROPOSED AC PAVEMENT AND OVERLAY
  - PROPOSED PCC
  - PROPOSED COLD MILL AND OVERLAY
  - PROPOSED AC

**NOTE:**  
1. SEE LANDSCAPE PLANS FOR VINYL RAIL FENCE INSTALLATION AND TREE REMOVAL LOCATIONS



PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
13191 CROSSROADS PARKWAY NORTH  
SUITE 405 INDUSTRY, CA 91746-3497  
(562) 908-6200  
UNDER THE SUPERVISION OF  
TYRONE PETER RCE No. 81888 DATE

BENCH MARK:  
NO. \_\_\_\_\_ ELEV. \_\_\_\_\_  
DATE ADJ. \_\_\_\_\_ QUAD. \_\_\_\_\_  
NONE

REVISIONS		
NO.	DESCRIPTION	APP. DATE

**CITY OF ROLLING HILLS ESTATES**

**STREET IMPROVEMENT PLAN AND PROFILE**




INTERSECTION CAPACITY IMPROVEMENTS  
AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

DRAWN BY: BR  
DESIGNED BY: BR  
CHECKED BY: FW

SHT. 5 OF 22 SHTS.

U:\110176 - RHE PVD\DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\PL-ROAD-01.dwg Apr 05, 23 - 10:18am

100% SUBMITTAL NOT FOR CONSTRUCTION



- CONSTRUCTION NOTES:**
- (16) CONSTRUCT CONCRETE DRAINAGE SWALE BEHIND RETAINING WALL PER SPPWC STD PLAN NO. 621-3
  - (17) CONSTRUCT RETAINING WALL, TYPE 7A, PER SPPWC STD PLAN NO. 616-3
  - (18) CONSTRUCT RETAINING WALL, TYPE 5, PER SPPWC STD PLAN NO. 614-3. CASE PER PLAN
  - (23) CONSTRUCT WALL GUTTER OUTLET TO CURB PER SPPWC STD PLAN NO. 617-3 AND PLAN No. 150-4
  - (24) CONSTRUCT CABLE RAILING PER CALTRANS STD B11-47, PER SECTION C-C

CURVE TABLE				
CURVE	LENGTH	RADIUS	DELTA	TANGENT
(1)	28.440	84.00	19°23'54"	14.36
(2)	34.192	100.84	19°25'39"	17.26

**LEGEND**  
 RETAINING WALL

PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
 13191 CROSSROADS PARKWAY NORTH  
 SUITE 405 INDUSTRY, CA 91746-3497  
 (562) 908-6200  
 UNDER THE SUPERVISION OF

BENCH MARK:  
 NO. \_\_\_\_\_ ELEV. \_\_\_\_\_  
 DATE ADJ. \_\_\_\_\_ QUAD. \_\_\_\_\_

NONE

REVISIONS		
NO.	DESCRIPTION	APP. DATE

**CITY OF ROLLING HILLS ESTATES**

**RETAINING WALL PLAN AND PROFILE**


INTERSECTION CAPACITY IMPROVEMENTS  
 AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

DRAWN BY: BR  
 DESIGNED BY: BR  
 CHECKED BY: FW

SHT. 6 OF 22 SHTS.

U:\110176 - RHE PVDN\DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\PL-RWAL-01.dwg Apr 05, 23 - 10:07am


100% SUBMITTAL NOT FOR CONSTRUCTION



RETAINING WALL No. 2 PROFILE AT LOL

RETAINING WALL No.3 PROFILE AT LOL

PROFILE SCALE  
HORIZ.: 1" = 20'  
VERT.: 1" = 8'




RETAINING WALL No.2 PLAN

RETAINING WALL No.3 PLAN

**CONSTRUCTION NOTES:**

- (16) CONSTRUCT CONCRETE DRAINAGE SWALE BEHIND RETAINING WALL PER SPPWC STD PLAN NO. 621-3
- (18) CONSTRUCT RETAINING WALL, TYPE 5, PER SPPWC STD PLAN NO. 614-3. CASE PER PLAN
- (19) CONSTRUCT RETAINING WALL, TYPE 5, MODIFIED PER DETAIL HEREON SPPWC STD PLAN NO. 614-3. CASE PER PLAN
- (22) CONSTRUCT WALL GUTTER OUTLET TO FACE OF WALL PER SPPWC STD PLAN NO. 617-3
- (24) CONSTRUCT CABLE RAILING PER CALTRANS STD B11-47, PER SECTION C-C

CURVE TABLE				
CURVE	LENGTH	RADIUS	DELTA	TANGENT
(3)	23.456	73.12	18°22'46"	11.83
(4)	30.926	73.12	24°13'59"	15.70



**LEGEND**  
 RETAINING WALL

PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
 13191 CROSSROADS PARKWAY NORTH  
 SUITE 405 INDUSTRY, CA 91746-3497  
 (562) 908-6200  
 UNDER THE SUPERVISION OF

BENCH MARK:  
 NO. \_\_\_\_\_ ELEV. \_\_\_\_\_  
 DATE ADJ. \_\_\_\_\_ QUAD. \_\_\_\_\_  
 NONE

REVISIONS		
NO.	DESCRIPTION	APP. DATE

**CITY OF ROLLING HILLS ESTATES**

**RETAINING WALL PLAN AND PROFILE**


INTERSECTION CAPACITY IMPROVEMENTS  
 AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

DRAWN BY: BR  
 DESIGNED BY: BR  
 CHECKED BY: FW


SHT. 7 OF 22 SHTS.

U:\110176 - RHE PVDN\DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\PL-RWAL-01.dwg Apr 05, 23 - 10:08am

100% SUBMITTAL NOT FOR CONSTRUCTION




7+50 8+00 8+50 9+00 9+50



RETAINING WALL No.3 PLAN


- CONSTRUCTION NOTES:**
- (16) CONSTRUCT CONCRETE DRAINAGE SWALE BEHIND RETAINING WALL PER SPPWC STD PLAN NO. 621-3
  - (18) CONSTRUCT RETAINING WALL, TYPE 5, PER SPPWC STD PLAN NO. 614-3. CASE PER PLAN
  - (19) CONSTRUCT RETAINING WALL, TYPE 5, MODIFIED PER DETAIL HEREON SPPWC STD PLAN NO. 614-3. CASE PER PLAN
  - (23) CONSTRUCT WALL GUTTER OUTLET TO CURB PER SPPWC STD PLAN NO. 617-3 AND PLAN No. 150-4
  - (24) CONSTRUCT CABLE RAILING PER CALTRANS STD B11-47, PER SECTION C-C



TYPE 5 MODIFIED RETAINING WALL

**LEGEND**

--- RETAINING WALL



**CITY OF ROLLING HILLS ESTATES**

**RETAINING WALL PLAN AND PROFILE**  
 INTERSECTION CAPACITY IMPROVEMENTS  
 AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
 13191 CROSSROADS PARKWAY NORTH  
 SUITE 405 INDUSTRY, CA 91746-3497  
 (562) 908-6200  
 UNDER THE SUPERVISION OF

BENCH MARK:  
 NO. \_\_\_\_\_ ELEV. \_\_\_\_\_  
 DATE ADJ. \_\_\_\_\_ QUAD. \_\_\_\_\_  
 NONE


REVISIONS		
NO.	DESCRIPTION	APP. DATE

DRAWN BY: BR  
 DESIGNED BY: BR  
 CHECKED BY: FW  
 SHT. 8 OF 22 SHTS.

U:\110176 - RHE PVDN\DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\PL-RWAL-01.dwg Apr 05, 23 - 10:08am

100% SUBMITTAL NOT FOR CONSTRUCTION






RETAINING WALL No.4 PROFILE AT LOL

PROFILE SCALE:  
HORIZ.: 1"=20'  
VERT.: 1"=8'



CONSTRUCTION NOTES:

- ⑤ CONSTRUCT RETAINING WALL PER DETAIL B ON SHEET 9



RETAINING WALL No.4 PLAN

CURVE TABLE				
CURVE	LENGTH	RADIUS	DELTA	TANGENT
5	136.009	959.61	8°07'15"	68.12
6	78.297	957.50	4°41'07"	39.17



LEGEND

■■■■■ RETAINING WALL

PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
13191 CROSSROADS PARKWAY NORTH  
SUITE 405 INDUSTRY, CA 91746-3497  
(562) 908-6200  
UNDER THE SUPERVISION OF \_\_\_\_\_

BENCH MARK:  
NO. \_\_\_\_\_ ELEV. \_\_\_\_\_  
DATE ADJ. \_\_\_\_\_ QUAD. \_\_\_\_\_  
NONE

REVISIONS		
NO.	DESCRIPTION	APP. DATE

**CITY OF ROLLING HILLS ESTATES**

**RETAINING WALL PLAN AND PROFILE**


INTERSECTION CAPACITY IMPROVEMENTS  
AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

DRAWN BY: BR  
DESIGNED BY: BR  
CHECKED BY: FW

SHT. 9 OF 22 SHTS.


U:\110176 - RHE PVDN\DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\PL-RWAL-01.dwg Apr 05, 23 - 10:08am

100% SUBMITTAL NOT FOR CONSTRUCTION



RETAINING WALL No.5 PROFILE AT LOL

PROFILE SCALE:  
HORIZ.: 1" = 20'  
VERT.: 1" = 8'




RETAINING WALL No.5 PLAN

**CONSTRUCTION NOTES:**

- ⑩ CONSTRUCT CONCRETE DRAINAGE SWALE BEHIND RETAINING WALL PER SPPWC STD PLAN NO. 621-3
- ⑪ CONSTRUCT RETAINING WALL, TYPE 7A, PER SPPWC STD PLAN NO. 616-3
- ⑫ CONSTRUCT WALL GUTTER OUTLET TO FACE OF WALL PER SPPWC STD PLAN NO. 617-3

**LEGEND**  
 RETAINING WALL



**CITY OF ROLLING HILLS ESTATES**

**RETAINING WALL PLAN AND PROFILE**

INTERSECTION CAPACITY IMPROVEMENTS  
AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

DRAWN BY: BR	SHT. 10 OF 22 SHTS.
DESIGNED BY: BR	
CHECKED BY: FW	

PLANS PREPARED BY: <b>WILLDAN Engineering</b> 13191 CROSSROADS PARKWAY NORTH SUITE 405 INDUSTRY, CA 91746-3497 (562) 908-6200 UNDER THE SUPERVISION OF _____	COMPREHENSIVE INNOVATIVE TRUSTED	BENCH MARK: NO. _____ ELEV. _____ DATE ADJ. _____ QUAD. _____  NONE	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="3">REVISIONS</th> </tr> <tr> <th>NO.</th> <th>DESCRIPTION</th> <th>APP. DATE</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>	REVISIONS			NO.	DESCRIPTION	APP. DATE						
REVISIONS															
NO.	DESCRIPTION	APP. DATE													



U:\110176 - RHE PVDN\DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\PL-RWAL-01.dwg Apr 05, 23 - 10:09am

100% SUBMITTAL NOT FOR CONSTRUCTION

No.	STANDARD			LUMINAIRE HPS	VEHICLE SIGNAL MOUNTING		PED SIGNAL	PPB		EPB*		POLE LOCATION (SEE DETAIL "A")			REMARKS	
	TYPE	LUM. M.A.	SIG. M.A.		MAST ARM	POLE		MTG.	Ø	QUAD	ARROW	Ø	QUAD	ARROW		E
(A)	SIGNAL STRUCTURE A	2'	45'	250W	MAS-5A, MAS	SV-3-TB	-	-	-	-	-	-	-	-	-	1., 2.
(B)	SIGNAL STRUCTURE B	-	-	-	-	SV-1-T	-	-	-	-	-	-	-	-	-	1., 2.
(C)	SIGNAL STRUCTURE C	2'	-	250W	-	SV-3-TB	SP-1-T	8	E	→	-	-	-	-	-	1., 2.
(D)	SIGNAL STRUCTURE D	2'	30'	250W	MAS	SV-2-TD	SP-2-T	8	W	→	-	-	-	-	-	1., 2.
(E)	SIGNAL STRUCTURE B	-	-	-	-	SV-3-TB	-	6	S	→	6	N	←	-	-	1., 2.
(F)	SIGNAL STRUCTURE C	2'	-	250W	-	-	-	6	S	→	6	N	←	-	-	1., 2.
(G)	SIGNAL STRUCTURE C	2'	-	250W	-	SV-1-T	SP-1-T	-	-	-	-	-	-	-	-	1., 2.

■ ALL EQUIPMENT IS NEW


1. MODIFIED FOUNDATION, SEE DETAILS ON SHEET 13.
2. TRAFFIC SIGNAL POLES ARE SQUARE DECORATIVE SIGNAL STRUCTURES, SEE DETAILS ON SHEET 12.



Ø5 SHALL NOT BE RE-SERVICED UNTIL SUCH TIME  
Ø2 AND Ø6 HAVE TERMINATED SIMULTANEOUSLY.


TRAFFIC SIGNAL GENERAL NOTES:

1. TRAFFIC SIGNAL AND HIGHWAY LIGHTING EQUIPMENT, SIGNING, AND THE INSTALLATION THEREOF SHALL CONFORM TO CALTRANS STANDARD PLANS AND SPECIFICATIONS, DATED 2018, THE CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (CALIFORNIA MUTCD), DATED 2014, THIS PLAN AND THE SPECIAL PROVISIONS.
2. NEW VEHICLE INDICATIONS SHALL BE 12" LED RED, LED AMBER AND LED GREEN PER CALTRANS APPROVED SPECIFICATIONS.
3. NEW SIGNAL HEADS SHALL BE METAL.
4. NEW CONDUIT SHALL BE MIN. SIZE 2" RIGID STEEL AND NEW PULL BOXES SHALL BE #5, UNLESS SHOWN OTHERWISE.
5. ALL PEDESTRIAN INDICATIONS SHALL BE LED COUNT-DOWN PEDESTRIAN HEADS (SEE SPECIAL PROVISIONS).
6. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY THE EXISTENCE AND LOCATION OF ALL OVERHEAD AND UNDERGROUND FACILITIES, AND TO PROTECT THEM FROM DAMAGE THE CONTRACTOR SHALL BEAR THE TOTAL EXPENSE OF REPAIR OR REPLACEMENT OF ANY OVERHEAD AND UNDERGROUND FACILITIES DAMAGED DURING CONSTRUCTION.
7. CONDUCTOR SCHEDULE IS PROVIDED AS AN INSTALLATION GUIDELINE ONLY. IT IS THE CONTRACTOR'S RESPONSIBILITY TO PROVIDE THE CORRECT CONDUCTORS REQUIRED FOR THE INTENDED OPERATION.
8. CONTRACTOR SHALL OBTAIN APPROVAL FROM THE CITY ENGINEER FOR EXACT EQUIPMENT LOCATION PRIOR TO FINAL PLACEMENT.
9. LOCATION OF UNDERGROUND FACILITIES ARE APPROXIMATE. THE CONTRACTOR SHALL POthOLE TO DETERMINE THE EXACT LOCATION AND VERIFY ALL CONDITIONS ON THE JOBSITE. HAND DIG FOUNDATIONS UNTIL CLEAR OF OBSTRUCTION. COORDINATE POLE INSTALLATION WITH OVERHEAD UTILITY AND SUBSTRUCTURE OWNERS. CONTACT UNDERGROUND SERVICE ALERT AT 811 OR (800) 227-2600, TWO (2) WORKING DAYS PRIOR TO CONSTRUCTION.
10. ANY MODIFICATION OF OR CHANGES TO APPROVED PLANS MUST BE APPROVED BY THE CITY ENGINEER.
11. CONTRACTOR SHALL REPLACE IN-KIND ANY PRIVATE FENCES, WALLS, LAWNS, SHRUBBERY, IRRIGATION, ETC. REMOVED OR DAMAGED TO FACILITATE TRAFFIC SIGNAL INSTALLATION, SIDEWALK, AND CURB CONSTRUCTION. CONTRACTOR SHALL MODIFY AND REPLACE IN-KIND ANY IRRIGATION DAMAGED OR REMOVED BY CONSTRUCTION TO MAINTAIN OPERATION.
12. COORDINATE ELECTRICAL SERVICE DETAILS AND SCHEDULING WITH SOUTHERN CALIFORNIA EDISON. CONTACT MR. RYAN KERBY AT (310) 783-9305.
13. ALL UNUSED AND/OR ABANDONED PULL BOXES AND FOUNDATIONS SHALL BE REMOVED AND THE AFFECTED AREA REPAIRED OR RESTORED TO MATCH SURROUNDING.
14. INDUCTIVE DETECTOR LOOPS SHALL BE 6' DIAMETER TYPE "E" AND CENTERED IN TRAVEL LANE WITH 10' SPACING BETWEEN LOOPS IN THE DIRECTION OF TRAVEL. LIMIT LINE LOOPS SHALL BE MODIFIED TYPE "D" BICYCLE DETECTOR LOOPS PER LOS ANGELES COUNTY STANDARDS. PLACE LIMIT LINE LOOPS 2' INTO CROSSWALK OR LIMIT LINE.
15. CONTRACTOR SHALL FURNISH AND INSTALL TEMPORARY EQUIPMENT NECESSARY TO MAINTAIN CURRENT SIGNAL OPERATION, INCLUDING BUT NOT LIMITED TO CONTROLLER ASSEMBLIES AND SIGNAL POLES.
16. EXISTING CONDUIT NOT SHOWN FOR REUSE SHALL BE ABANDONED AND CONDUCTORS REMOVED.
17. CONTRACTOR SHALL BE RESPONSIBLE FOR FURNISHING ANY TEMPORARY TRAFFIC SIGNAL INSTALLATION OF CABINETS, POLES, OR CONDUITS WITH ALL NECESSARY TRAFFIC SIGNAL EQUIPMENT INCLUDING TEMPORARY OVERHEAD WIRING DURING CONSTRUCTION. THE SIGNALIZED TRAFFIC INTERSECTION SHALL BE FULLY OPERATIONAL AT ALL TIMES.
18. ALL EQUIPMENT TO BE REMOVED SHALL BE DISPOSED OF BY THE CONTRACTOR.



AWG	CONDUCTOR SCHEDULE ▲						
	CIRCUIT	1	2	3	4	5	6
1/2 CONDUCTOR CABLE	POLE (A)	2	1	1	1	1	1
	POLE (B)	1	1	1	1	1	1
	POLE (C)	2	2	2	2	2	2
	POLE (D)	2	2	2	2	2	2
	POLE (E)	2	2	2	2	2	2
	POLE (F)	2	2	2	2	2	2
	POLE (G)	1	1	1	1	1	1
TOTAL	8	6	6	6	6	6	
#10 LUMINAIRE	-	2	2	2	-	2	2
Ø2 DETECTOR	3	3	3	-	-	-	
Ø5 DETECTOR	1	1	1	-	-	-	
Ø6 DETECTOR	3	3	3	3	-	3	
Ø8 DETECTOR	4	4	4	4	4	-	
TOTAL	10	10	10	7	4	3	
CONDUIT SIZE	2-4"	2-4"	2-4"	4"	2"	4"	
% FILL	18	16	14	19	17	8	

▲ ALL CONDUCTORS AND CONDUIT ARE NEW. SEE GENERAL NOTE NO. 7



CONSTRUCTION NOTES:

1. INSTALL NEW ECONOLITE TS2 TYPE P CABINET COMPLETE WITH ECONOLITE ASC/3-2100 CONTROLLER ASSEMBLY, BATTERY BACKUP SYSTEM, GPS ANTENNA, GPS UNIT, AND ALL AUXILIARY EQUIPMENT NECESSARY TO PROVIDE THE OPERATION SHOWN. CONSTRUCT NEW FOUNDATION. TOP OF FOUNDATION SHALL BE 18" ABOVE FINISHED GRADE.
2. REMOVE EXISTING TYPE P CONTROLLER CABINET COMPLETE, BATTERY BACKUP AND TYPE II SERVICE CABINET
3. INSTALL 120/240V TYPE III-BF ELECTRICAL SERVICE ENCLOSURE WITH 1-100 AMP METER, PROVIDE 1-50 AMP BREAKER FOR METERED SIGNAL, AND 1-30AMP BREAKER FOR UNMETERED LUMINAIRES. LOCATE ENCLOSURE A MINIMUM OF 6' FROM THE CONTROLLER CABINET AND POWER POLE.
4. REMOVE EXISTING POLE COMPLETE.
5. INSTALL SIGN(S) AS SHOWN.
6. INSTALL 3" SCHEDULE 80 PVC CONDUIT WITH PULL ROPE AND REUSE EXISTING SERVICE RISER PER SCE REQUIREMENTS. COORDINATE INSTALLATION WITH EDISON SERVICE PLANNER RYAN KERBY AT (310) 783-9305 48 HOURS PRIOR TO CONSTRUCTION.



PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
13191 CROSSROADS PARKWAY NORTH  
SUITE 405 INDUSTRY, CA 91746-3497  
(562) 908-6200  
UNDER THE SUPERVISION OF  
JEFFREY LAU, RCE No. 83887 DATE

BENCH MARK:	NONE	
NO. _____ ELEV. _____	NO. _____	DATE _____
DATE ADJ. _____ QUAD. _____	NO. _____	DATE _____

**CITY OF ROLLING HILLS ESTATES**

**TRAFFIC SIGNAL MODIFICATION PLAN**

INTERSECTION CAPACITY IMPROVEMENTS  
AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

NO.	REVISIONS	DESCRIPTION	APP.	DATE

DRAWN BY: RG/KC  
DESIGNED BY: RG/KC  
CHECKED BY: JL

SHT. 11 OF 22 SHTS.

U:\110176 - RHE PVD\DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\PL-SIGNAL-01.dwg Apr 03, 23 - 1:22pm

100% SUBMITTAL NOT FOR CONSTRUCTION

SCALE: 1"=20'

100% SUBMITTAL NOT FOR CONSTRUCTION

### DETAIL "A" & DETAIL "D" TRAFFIC SIGNAL STRUCTURE A TRAFFIC SIGNAL STRUCTURE D

**DETAIL 1 - POLE TOP**  
HOOK FOR WIRING & HANDLING 0.38" DIA. COMMERCIAL GRADE HOT ROLLED BAR  
CAPS PROVIDED BY OTHERS AND FIELD INSTALLED.

**DETAIL 2 - LUMINAIRE ARM END CAP**  
SQUARE, 0.50" THICK COMMERCIAL QUALITY HOT ROLLED MILD STEEL ARM END CAP.  
MOUNTING CLIP  
(2) -0.25" HEX HEAD SCREW

**DETAIL 3 - LUMINAIRE ARM END**  
3.00" - 6.00" - 0.50" - 0.25" - 0.38" DIA. TAPPED HOLE (2-REG'D)

**DETAIL 4 - SIGNAL ARM ATTACHMENT**  
(4) -0.25" THICK COMMERCIAL QUALITY HOT ROLLED MILD STEEL ARM END CAP.  
MOUNTING CLIP  
(2) -0.25" HEX HEAD SCREW

**DETAIL 5 - POLE TOP**  
SQUARE, 0.50" THICK COMMERCIAL QUALITY HOT ROLLED MILD STEEL ARM END CAP.  
MOUNTING CLIP  
(2) -0.25" HEX HEAD SCREW

**DETAIL 6 - MAST ARM END CAP**  
SQUARE, 0.50" THICK COMMERCIAL QUALITY HOT ROLLED MILD STEEL ARM END CAP.  
MOUNTING CLIP  
(2) -0.25" HEX HEAD SCREW

**DETAIL 7 - SIGNAL ARM TENON**  
ARM TUBE  
4.00" - 1.75" - 0.44" DIA. THRU HOLE  
3.38" O.D. X 0.154" WALL X 5.00" LONG-PIPE SIZE TUBING

**DETAIL 8 - SCROLL**  
1.00" HEX HEAD BOLT AND NUT (2 REG'D)  
1.38" - 0.50" - 0.38" (TYP)

**DETAIL 9 - MAST ARM END CAP**  
SQUARE, 0.50" THICK COMMERCIAL QUALITY HOT ROLLED MILD STEEL ARM END CAP.  
MOUNTING CLIP  
(2) -0.25" HEX HEAD SCREW

**DETAIL 10 - POLE BASE**  
2.25" THICK BACK-UP RING  
1.50" RAD. - BOLT CIRCLE "Y"

**DETAIL 11 - ANCHOR BOLT**  
(4) ANCHOR BOLTS WITH (4) HEX NUTS AND (4) WASHERS PER BOLT FULLY GALVANIZED  
SEE DETAIL 12

**DETAIL 12 - ANCHOR BEARING PLATE**  
BOLT CIRCLE  
ITEM "L" "L" "L" "L"  
1.24.00(13.00")  
2.20.00(11.00")

**ORIENTATIONS**  
ANCHOR BOLT 45°  
HANDHOLE  
ALL ANGLES MEASURED CLOCKWISE FROM HAND HOLE AS VIEWED FROM SMALL END OF POLE

**MATERIAL DATA**

COMPONENT	ASTM DESIGNATION	MIN. YIELD (KSI)
POLE SHAFT	A572 GR. 65	65
PLATES	A36	50
BASE PLATES	A36	36
ANCHOR BOLTS	F1554 GR. 55	55
ANCHOR BOLT NUTS	F1554 GR. 55	55
ANCHOR BOLT WASHERS	A153	55

**FINISH DATA**  
SYSTEM: HOT-DIP GALVANIZED TO ASTM A123  
BASE COAT: HIGH BUILD EPOXY POWDER  
FINISH COAT: TGIC POWDER  
COLOR: WHITE  
SPEC: F-540A

**VIBRATION DISCLAIMER**  
ALTHOUGH RARE, VIBRATIONS SEVERE ENOUGH TO CAUSE DAMAGE CAN OCCASIONALLY OCCUR IN STRUCTURES OF ALL TYPES. BECAUSE THEY ARE INFLUENCED BY MANY INTERACTING VARIABLES, VIBRATIONS ARE GENERALLY UNPREDICTABLE. THE USER'S MAINTENANCE PROGRAM SHOULD INCLUDE OBSERVATION FOR EXCESSIVE VIBRATION AND EXAMINATION FOR ANY STRUCTURAL DAMAGE OR BOLT LOOSENING. THE VALMONT WARRANTY SPECIFICALLY EXCLUDES FATIGUE FAILURE OR SIMILAR PHENOMENA RESULTING FROM INDUCED VIBRATION, HARMONIC OSCILLATION OR RESONANCE ASSOCIATED WITH MOVEMENT OF AIR CURRENTS AROUND THE PRODUCT.

**POLE AND SIGNAL ARM DATA**

ITEM	QTY.	POLE TUBE		POLE BASE		ANCHOR BOLT		SIGNAL ARM TUBE										
		BASE SQ. (IN)	TOP SQ. (IN)	LENGTH (FT)	GAUGE OR THK. (IN)	SQUARE "S" (IN)	BOLT CIRCLE "Y" (IN)	THK. "M" (IN)	HOLE "Z" (IN)	DIA. "K" (IN)	LENGTH "L" (IN)	THREAD LENGTH "U" (IN)	FIXED END SQ. (IN)	FREE END SQ. (IN)	GAUGE OR THK. (IN)	SPAN (FT)	"P" (FT)	
1	1	14.00	9.80	30.00	0.375	24.00	22.00	2.00	2.00	1.75	84.00	9.00	4.00	10.00	10.00	0.250	45.00	15.00
2	1	12.00	7.80	30.00	0.375	22.00	20.00	2.00	1.75	1.50	54.00	8.00	4.00	8.00	8.00	0.188	6.00	4.00

**SIGNAL ARM ATTACHMENT DATA - 4 BOLT**

MAST ARM SPAN (FT)	"A" (IN)	"B" (IN)	"C" (IN)	"D" (IN)	"E" (IN)	"F" (IN)
30.00	16.00	11.00	12.00	7.75	1.75	1.25 X 3.50
45.00	18.50	15.50	15.00	12.00	2.00	1.25 X 4.00

**VALMONT INDUSTRIES, INC. RESERVES THE RIGHT TO INSTALL VARIOUS ENGINEER APPROVED, MATERIAL HANGING ACCOMMODATIONS TO FACILITATE THE MANUFACTURING PROCESS.**

**valmont**  
Valley, NE 68064  
(402) 399-2201

ORDER NUMBER: 517241-P1  
PAGE NUMBER: 1 OF 5  
DRAWING NUMBER: REV  
TITLE: TRAFFIC SIGNAL STRUCTURES  
CAS17241P1 A

### DETAIL "A" & DETAIL "D" TRAFFIC SIGNAL STRUCTURE A TRAFFIC SIGNAL STRUCTURE D

**DETAIL 1 - POLE TOP**  
HOOK FOR WIRING & HANDLING 0.38" DIA. COMMERCIAL GRADE HOT ROLLED BAR  
CAPS PROVIDED BY OTHERS AND FIELD INSTALLED.

**DETAIL 2 - LUMINAIRE ARM END CAP**  
SQUARE, 0.50" THICK COMMERCIAL QUALITY HOT ROLLED MILD STEEL ARM END CAP.  
MOUNTING CLIP  
(2) -0.25" HEX HEAD SCREW

**DETAIL 3 - LUMINAIRE ARM END**  
3.00" - 6.00" - 0.50" - 0.25" - 0.38" DIA. TAPPED HOLE (2-REG'D)

**DETAIL 4 - SIGNAL ARM ATTACHMENT**  
(4) -0.25" THICK COMMERCIAL QUALITY HOT ROLLED MILD STEEL ARM END CAP.  
MOUNTING CLIP  
(2) -0.25" HEX HEAD SCREW

**DETAIL 5 - POLE TOP**  
SQUARE, 0.50" THICK COMMERCIAL QUALITY HOT ROLLED MILD STEEL ARM END CAP.  
MOUNTING CLIP  
(2) -0.25" HEX HEAD SCREW

**DETAIL 6 - MAST ARM END CAP**  
SQUARE, 0.50" THICK COMMERCIAL QUALITY HOT ROLLED MILD STEEL ARM END CAP.  
MOUNTING CLIP  
(2) -0.25" HEX HEAD SCREW

**DETAIL 7 - SIGNAL ARM TENON**  
ARM TUBE  
4.00" - 1.75" - 0.44" DIA. THRU HOLE  
3.38" O.D. X 0.154" WALL X 5.00" LONG-PIPE SIZE TUBING

**DETAIL 8 - SCROLL**  
1.00" HEX HEAD BOLT AND NUT (2 REG'D)  
1.38" - 0.50" - 0.38" (TYP)

**DETAIL 9 - MAST ARM END CAP**  
SQUARE, 0.50" THICK COMMERCIAL QUALITY HOT ROLLED MILD STEEL ARM END CAP.  
MOUNTING CLIP  
(2) -0.25" HEX HEAD SCREW

**DETAIL 10 - POLE BASE**  
2.25" THICK BACK-UP RING  
1.50" RAD. - BOLT CIRCLE "Y"

**DETAIL 11 - ANCHOR BOLT**  
(4) ANCHOR BOLTS WITH (4) HEX NUTS AND (4) WASHERS PER BOLT FULLY GALVANIZED  
SEE DETAIL 12

**DETAIL 12 - ANCHOR BEARING PLATE**  
BOLT CIRCLE  
ITEM "L" "L" "L" "L"  
1.24.00(13.00")  
2.20.00(11.00")

**ORIENTATIONS**  
ANCHOR BOLT 45°  
HANDHOLE  
ALL ANGLES MEASURED CLOCKWISE FROM HAND HOLE AS VIEWED FROM SMALL END OF POLE

**MATERIAL DATA**

COMPONENT	ASTM DESIGNATION	MIN. YIELD (KSI)
POLE SHAFT	A572 GR. 65	65
PLATES	A36	50
BASE PLATES	A36	36
ANCHOR BOLTS	F1554 GR. 55	55
ANCHOR BOLT NUTS	F1554 GR. 55	55
ANCHOR BOLT WASHERS	A153	55

**FINISH DATA**  
SYSTEM: HOT-DIP GALVANIZED TO ASTM A123  
BASE COAT: HIGH BUILD EPOXY POWDER  
FINISH COAT: TGIC POWDER  
COLOR: WHITE  
SPEC: F-540A

**VIBRATION DISCLAIMER**  
ALTHOUGH RARE, VIBRATIONS SEVERE ENOUGH TO CAUSE DAMAGE CAN OCCASIONALLY OCCUR IN STRUCTURES OF ALL TYPES. BECAUSE THEY ARE INFLUENCED BY MANY INTERACTING VARIABLES, VIBRATIONS ARE GENERALLY UNPREDICTABLE. THE USER'S MAINTENANCE PROGRAM SHOULD INCLUDE OBSERVATION FOR EXCESSIVE VIBRATION AND EXAMINATION FOR ANY STRUCTURAL DAMAGE OR BOLT LOOSENING. THE VALMONT WARRANTY SPECIFICALLY EXCLUDES FATIGUE FAILURE OR SIMILAR PHENOMENA RESULTING FROM INDUCED VIBRATION, HARMONIC OSCILLATION OR RESONANCE ASSOCIATED WITH MOVEMENT OF AIR CURRENTS AROUND THE PRODUCT.

**POLE AND SIGNAL ARM DATA**

ITEM	QTY.	POLE TUBE		POLE BASE		ANCHOR BOLT		SIGNAL ARM TUBE										
		BASE SQ. (IN)	TOP SQ. (IN)	LENGTH (FT)	GAUGE OR THK. (IN)	SQUARE "S" (IN)	BOLT CIRCLE "Y" (IN)	THK. "M" (IN)	HOLE "Z" (IN)	DIA. "K" (IN)	LENGTH "L" (IN)	THREAD LENGTH "U" (IN)	FIXED END SQ. (IN)	FREE END SQ. (IN)	GAUGE OR THK. (IN)	SPAN (FT)	"P" (FT)	
1	1	14.00	9.80	30.00	0.375	24.00	22.00	2.00	2.00	1.75	84.00	9.00	4.00	10.00	10.00	0.250	45.00	15.00
2	1	12.00	7.80	30.00	0.375	22.00	20.00	2.00	1.75	1.50	54.00	8.00	4.00	8.00	8.00	0.188	6.00	4.00

**SIGNAL ARM ATTACHMENT DATA - 4 BOLT**

MAST ARM SPAN (FT)	"A" (IN)	"B" (IN)	"C" (IN)	"D" (IN)	"E" (IN)	"F" (IN)
30.00	16.00	11.00	12.00	7.75	1.75	1.25 X 3.50
45.00	18.50	15.50	15.00	12.00	2.00	1.25 X 4.00

**VALMONT INDUSTRIES, INC. RESERVES THE RIGHT TO INSTALL VARIOUS ENGINEER APPROVED, MATERIAL HANGING ACCOMMODATIONS TO FACILITATE THE MANUFACTURING PROCESS.**

**valmont**  
Valley, NE 68064  
(402) 399-2201

ORDER NUMBER: 517241-P1  
PAGE NUMBER: 2 OF 5  
DRAWING NUMBER: REV  
TITLE: TRAFFIC SIGNAL STRUCTURES  
CAS17241P1 A

### DETAIL "B" TRAFFIC SIGNAL STRUCTURE B

**DETAIL 1 - POLE TOP**  
HOOK FOR WIRING & HANDLING 0.38" DIA. COMMERCIAL GRADE HOT ROLLED BAR  
CAPS PROVIDED BY OTHERS AND FIELD INSTALLED.

**DETAIL 2 - 3"x5" HANDHOLE**  
COVER ATTACHMENT LUB = 7 GA. X 1" H.R.M.S. BAR  
0.25" X 3" PAN HEAD MACHINE SCREW  
0.50" NUT HOLDER WITH FASTENERS FOR GROUNDING.

**DETAIL 3 - POLE BASE**  
(4) ANCHOR BOLTS WITH (4) HEX NUTS AND (4) WASHERS PER BOLT FULLY GALVANIZED  
SEE DETAIL 5

**DETAIL 4 - ANCHOR BOLT**  
12.00" - 6.00" - 0.50" - BOLT CIRCLE  
ANCHOR BOLT DIAMETER + 0.06

**DETAIL 5 - ANCHOR BEARING PLATE**  
ANCHOR BOLT 45°  
HANDHOLE  
ALL ANGLES MEASURED CLOCKWISE FROM HAND HOLE AS VIEWED FROM SMALL END OF POLE

**DETAIL 6 - ANCHOR BOLT**  
(4) ANCHOR BOLTS WITH (4) HEX NUTS AND (4) WASHERS PER BOLT FULLY GALVANIZED  
SEE DETAIL 7

**DETAIL 7 - ANCHOR BEARING PLATE**  
BOLT CIRCLE  
ITEM "L" "L" "L" "L"  
1.24.00(13.00")  
2.20.00(11.00")

**ORIENTATIONS**  
ANCHOR BOLT 45°  
HANDHOLE  
ALL ANGLES MEASURED CLOCKWISE FROM HAND HOLE AS VIEWED FROM SMALL END OF POLE

**MATERIAL DATA**

COMPONENT	ASTM DESIGNATION	MIN. YIELD (KSI)
POLE SHAFT	A572 GR. 65	65
PLATES	A36	50
BASE PLATES	A36	36
ANCHOR BOLTS	F1554 GR. 55	55
ANCHOR BOLT NUTS	F1554 GR. 55	55
ANCHOR BOLT WASHERS	A153	55

**FINISH DATA**  
SYSTEM: HOT-DIP GALVANIZED TO ASTM A123  
BASE COAT: HIGH BUILD EPOXY POWDER  
FINISH COAT: TGIC POWDER  
COLOR: WHITE  
SPEC: F-540A

**VIBRATION DISCLAIMER**  
ALTHOUGH RARE, VIBRATIONS SEVERE ENOUGH TO CAUSE DAMAGE CAN OCCASIONALLY OCCUR IN STRUCTURES OF ALL TYPES. BECAUSE THEY ARE INFLUENCED BY MANY INTERACTING VARIABLES, VIBRATIONS ARE GENERALLY UNPREDICTABLE. THE USER'S MAINTENANCE PROGRAM SHOULD INCLUDE OBSERVATION FOR EXCESSIVE VIBRATION AND EXAMINATION FOR ANY STRUCTURAL DAMAGE OR BOLT LOOSENING. THE VALMONT WARRANTY SPECIFICALLY EXCLUDES FATIGUE FAILURE OR SIMILAR PHENOMENA RESULTING FROM INDUCED VIBRATION, HARMONIC OSCILLATION OR RESONANCE ASSOCIATED WITH MOVEMENT OF AIR CURRENTS AROUND THE PRODUCT.

**POLE DATA**

ITEM DESCRIPTION	QTY.	POLE TUBE		POLE BASE		ANCHOR BOLT						
		BASE SQ. (IN)	TOP SQ. (IN)	LENGTH (FT)	GAUGE OR THK. (IN)	SQUARE "S" (IN)	BOLT CIRCLE "Y" (IN)	THK. "M" (IN)	HOLE / SLOT "Z" (IN)	DIA. "K" (IN)	LENGTH "L" (IN)	THREAD LENGTH "U" (IN)
CUSTOM SQUARE TYPE 1-14"	1	6.00	6.00	14.00	0.179	12.00	12.50	1.00	1.25	1.00	36.00	6.00

**VALMONT INDUSTRIES, INC. RESERVES THE RIGHT TO INSTALL VARIOUS ENGINEER APPROVED, MATERIAL HANGING ACCOMMODATIONS TO FACILITATE THE MANUFACTURING PROCESS.**

**valmont**  
Valley, NE 68064  
(402) 399-2201

ORDER NUMBER: 517241-P1  
PAGE NUMBER: 3 OF 5  
DRAWING NUMBER: REV  
TITLE: TRAFFIC SIGNAL STRUCTURES  
CAS17241P1 A

### DETAIL "C" TRAFFIC SIGNAL STRUCTURE C

**DETAIL 1 - POLE TOP**  
HOOK FOR WIRING & HANDLING 0.38" DIA. COMMERCIAL GRADE HOT ROLLED BAR  
CAPS PROVIDED BY OTHERS AND FIELD INSTALLED.

**DETAIL 2 - LUMINAIRE ARM END CAP**  
SQUARE, 0.50" THICK COMMERCIAL QUALITY HOT ROLLED MILD STEEL ARM END CAP.  
MOUNTING CLIP  
(2) -0.25" HEX HEAD SCREW

**DETAIL 3 - LUMINAIRE ARM END**  
3.00" - 6.00" - 0.50" - 0.25" - 0.38" DIA. TAPPED HOLE (2-REG'D)

**DETAIL 4 - SIGNAL ARM ATTACHMENT**  
(4) -0.25" THICK COMMERCIAL QUALITY HOT ROLLED MILD STEEL ARM END CAP.  
MOUNTING CLIP  
(2) -0.25" HEX HEAD SCREW

**DETAIL 5 - POLE TOP**  
SQUARE, 0.50" THICK COMMERCIAL QUALITY HOT ROLLED MILD STEEL ARM END CAP.  
MOUNTING CLIP  
(2) -0.25" HEX HEAD SCREW

**DETAIL 6 - MAST ARM END CAP**  
SQUARE, 0.50" THICK COMMERCIAL QUALITY HOT ROLLED MILD STEEL ARM END CAP.  
MOUNTING CLIP  
(2) -0.25" HEX HEAD SCREW

**DETAIL 7 - SIGNAL ARM TENON**  
ARM TUBE  
4.00" - 1.75" - 0.44" DIA. THRU HOLE  
3.38" O.D. X 0.154" WALL X 5.00" LONG-PIPE SIZE TUBING

**DETAIL 8 - SCROLL**  
1.00" HEX HEAD BOLT AND NUT (2 REG'D)  
1.38" - 0.50" - 0.38" (TYP)

**DETAIL 9 - MAST ARM END CAP**  
SQUARE, 0.50" THICK COMMERCIAL QUALITY HOT ROLLED MILD STEEL ARM END CAP.  
MOUNTING CLIP  
(2) -0.25" HEX HEAD SCREW

**DETAIL 10 - POLE BASE**  
2.25" THICK BACK-UP RING  
1.50" RAD. - BOLT CIRCLE "Y"

**DETAIL 11 - ANCHOR BOLT**  
(4) ANCHOR BOLTS WITH (4) HEX NUTS AND (4) WASHERS PER BOLT FULLY GALVANIZED  
SEE DETAIL 12

**DETAIL 12 - ANCHOR BEARING PLATE**  
BOLT CIRCLE  
ITEM "L" "L" "L" "L"  
1.24.00(13.00")  
2.20.00(11.00")

**ORIENTATIONS**  
ANCHOR BOLT 45°  
HANDHOLE  
ALL ANGLES MEASURED CLOCKWISE FROM HAND HOLE AS VIEWED FROM SMALL END OF POLE

**MATERIAL DATA**

COMPONENT	ASTM DESIGNATION	MIN. YIELD (KSI)
POLE SHAFT	A572 GR. 65	65
PLATES	A36	50
BASE PLATES	A36	36
ANCHOR BOLTS	F1554 GR. 55	55
ANCHOR BOLT NUTS	F1554 GR. 55	55
ANCHOR BOLT WASHERS	A153	55

**FINISH DATA**  
SYSTEM: HOT-DIP GALVANIZED TO ASTM A123  
BASE COAT: HIGH BUILD EPOXY POWDER  
FINISH COAT: TGIC POWDER  
COLOR: WHITE  
SPEC: F-540A

**VIBRATION DISCLAIMER**  
ALTHOUGH RARE, VIBRATIONS SEVERE ENOUGH TO CAUSE DAMAGE CAN OCCASIONALLY OCCUR IN STRUCTURES OF ALL TYPES. BECAUSE THEY ARE INFLUENCED BY MANY INTERACTING VARIABLES, VIBRATIONS ARE GENERALLY UNPREDICTABLE. THE USER'S MAINTENANCE PROGRAM SHOULD INCLUDE OBSERVATION FOR EXCESSIVE VIBRATION AND EXAMINATION FOR ANY STRUCTURAL DAMAGE OR BOLT LOOSENING. THE VALMONT WARRANTY SPECIFICALLY EXCLUDES FATIGUE FAILURE OR SIMILAR PHENOMENA RESULTING FROM INDUCED VIBRATION, HARMONIC OSCILLATION OR RESONANCE ASSOCIATED WITH MOVEMENT OF AIR CURRENTS AROUND THE PRODUCT.

**POLE AND SIGNAL ARM DATA**

ITEM	QTY.	POLE TUBE		POLE BASE		ANCHOR BOLT		SIGNAL ARM TUBE										
		BASE SQ. (IN)	TOP SQ. (IN)	LENGTH (FT)	GAUGE OR THK. (IN)	SQUARE "S" (IN)	BOLT CIRCLE "Y" (IN)	THK. "M" (IN)	HOLE "Z" (IN)	DIA. "K" (IN)	LENGTH "L" (IN)	THREAD LENGTH "U" (IN)	FIXED END SQ. (IN)	FREE END SQ. (IN)	GAUGE OR THK. (IN)	SPAN (FT)	"P" (FT)	
1	1	6.00	6.00	30.00	0.188	15.00	14.50	1.50	1.25	1.00	36.00	6.00	4.00	10.00	10.00	0.250	45.00	15.00

**SIGNAL ARM ATTACHMENT DATA - 4 BOLT**

MAST ARM SPAN (FT)	"A" (IN)	"B" (IN)	"C" (IN)	"D" (IN)	"E" (IN)	"F" (IN)
30.00	16.00	11.00	12.00	7.75	1.75	1.25 X 3.50
45.00	18.50	15.50	15.00	12.00	2.00	1.25 X 4.00

**VALMONT INDUSTRIES, INC. RESERVES THE RIGHT TO INSTALL VARIOUS ENGINEER APPROVED, MATERIAL HANGING ACCOMMODATIONS TO FACILITATE THE MANUFACTURING PROCESS.**

**valmont**  
Valley, NE 68064  
(402) 399-2201

ORDER NUMBER: 517241-P1  
PAGE NUMBER: 4 OF 5  
DRAWING NUMBER: REV  
TITLE: TRAFFIC SIGNAL STRUCTURES  
CAS17241P1 A

**CITY OF ROLLING HILLS ESTATES**

**TRAFFIC SIGNAL DECORATIVE POLE DETAILS**

INTERSECTION CAPACITY IMPROVEMENTS  
AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

BENCH MARK:		REVISIONS	
NO.	DESCRIPTION	NO.	DATE

DRAWN BY: BR  
DESIGNED BY: BR  
CHECKED BY: FW

SHT. 12 OF 22 SHTS.

PLANS PREPARED BY:

**WILLDAN Engineering** *Comprehensive Innovative Trusted*


13191 CROSSROADS PARKWAY NORTH  
SUITE 405 INDUSTRY, CA 91746-3497  
(562) 908-6200

UNDER THE SUPERVISION OF

JEFFREY LAU, RCE No. 83887 DATE



U:\110176 - RHE PVD\DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\PL-SIGNAL-02.dwg Apr 03, 23 1:23pm



1. FOUNDATION HOLE SHALL BE AUGERED AND FILLED WITH CONCRETE. CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH (F<sub>C</sub>) OF 3000 PSI MINIMUM AT 28 DAYS. CONCRETE SHALL HAVE A MAXIMUM SLUMP OF 4" AS DETERMINED BY ASTM C143.

2. REINFORCING STEEL SHALL BE IN ACCORDANCE WITH ASTM A615 GRADE 60 OR EQUAL.

3. GEOTECHNICAL REPORT WAS NOT MADE. FOUNDATION IS DESIGNED ASSUMING A NON-COHESIVE SOIL. SOIL HAS A POSSIBILITY OF BEING HEAVILY SENSITIVE TO MOISTURE CONTENT AND MAY HAVE POOR SHRINKAGE AND SWELLING CHARACTERISTICS. CONTRACTOR SHALL CONTACT GEOTECHNICAL ENGINEER WITH SOIL CONDITIONS.

4. IF SOIL CONDITIONS DURING CONSTRUCTION DO NOT MEET THE DESCRIPTION GIVEN ABOVE OR IF SOLID BEDROCK IS REACHED BEFORE REACHING THE SPECIFIED EMBEDMENT DEPTH CONTACT VALMONT ENGINEERING BEFORE CONTINUING EXCAVATION.

5. FOUNDATION TO BE CAST AGAINST UNDISTURBED SOIL. IF CASINGS ARE REQUIRED TO PREVENT CAVING OF THE PIER THE CASING SHALL BE PULLED AFTER USE.

6. FOUNDATION TO BE POURED MONOLITHICALLY. DUE TO THE POSSIBILITY OF EXISTING SENSITIVE SOILS THE CONCRETE SHALL BE POURED THE SAME DAY AS THE EXCAVATION.

7. FOUNDATION DESIGN IS BASED ON WATER TABLE BEING BELOW THE BOTTOM OF THE PIER. CONSTRUCTION BELOW THE WATER TABLE MAY REQUIRE SPECIAL CONSTRUCTION TECHNIQUES TO PREVENT RUPURING DUE TO HYDROSTATIC PRESSURE.

8. SITE GRADE IS 7H TO 1V OR FLATTER.

9. NO CONDUIT. LAYOUT IS SHOWN. CONDUIT BY OTHERS.

10. CONSTRUCTION SHALL BE DONE IN ACCORDANCE WITH OSHA REQUIREMENTS WITH REGARDS TO WORKER ACCESS TO THE EXCAVATION.

11. PROVIDE 3" MINIMUM CONCRETE COVER ON ALL FACES.

12. SITE REQUIREMENTS MAY ADJUST TOP OF FOOTING ABOVE GRADE. CONTRACTOR SHALL FOLLOW PROJECT REQUIREMENTS. CONTRACTOR SHALL DETERMINE TOP OF FOOTING AND ADJUST CONCRETE AND REINFORCING STEEL QUANTITIES. SITE SPECIFIC REQUIREMENTS MUST BE REVIEWED.

13. ALL MATERIALS AND CONSTRUCTION SHALL CONFORM TO THE REQUIREMENTS OF THE LATEST ACT SPECIFICATIONS. LATEST DESIGN CODES, AND LOCAL CODES.

14. CONDUIT SHALL PROJECT A MINIMUM OF 2" ABOVE THE FOUNDATION. MAXIMUM PROJECTION SHALL BE 4".

15. ALL METHODS OF CONSTRUCTION AND INSTALLATION ARE THE RESPONSIBILITY OF THE CONTRACTOR.

16. NO OTHER LOADING CONDITIONS WERE CONSIDERED AND DESIGN IS BASED ON WIND LOADS ONLY.

17. CONTRACTOR SHALL FOLLOW STATE AND LOCAL SPECIFICATIONS.

GENERAL NOTES

FOUNDATION LOADS HAVE BEEN CALCULATED BASED ON AN ASSUMED 100 MPH WIND. AN OVERTURNING (FS = 2.0) AND TORSIONAL (FS = 1.1) WERE USED IN DESIGN.

CONTRACTOR TO VERIFY NUMBER OF ANCHOR BOLTS, SIZE AND BOLT CIRCLE.

NON-COHESIVE LOOSE/MEDIUM SOIL LAYER  
 $\phi = 30^\circ$  ASSUMED  
 $\gamma = 90$  PCF ASSUMED  
 $u = 0.25$  (FRICTION FACTOR)

SOIL DATA IS BASED UPON STANDARD SOIL PARAMETERS USED. CONTRACTOR TO CONFIRM SOIL CONDITIONS ON SITE. UPPER 1'-0" PROVIDES NO PASSIVE RESISTANCE.

SOIL DATA

AXIAL = 4794 LB  
 SHEAR = 4094 LB  
 SHEAR = 0 LB  
 MOMENT = 0 FT-LB  
 MOMENT = 71,440 FT-LB  
 TORSION = 42,860 FT-LB (NOMINAL FOR DESIGN)


FOUNDATION LOADS

POLE	CAISSON DATA (EA)		LONGITUDINAL BARS (EA)		TRANSVERSE BARS (EA)	
	DIA (FT)	EMBED (FT)	NL (DIA)	SL (SIZE)	(SIZE)	
MA	3.5	11.5	12	8	#4 TIES @ 6" TOP 9.5' #4 TIES @ 12" LOWER 6.5'	

SPECIAL SQ TRAFFIC POLES

DETAIL "A" & DETAIL "D"  
 FOUNDATION DESIGN FOR  
 TRAFFIC SIGNAL STRUCTURE A  
 TRAFFIC SIGNAL STRUCTURE D

OWNER	ROLLING HILLS ESTATES DECO TRAFFIC	VALMONT INDUSTRIES, INC. RESERVES THE RIGHT TO INSTALL VARIOUS ENGINEER APPROVED, MATERIAL HANGING ACCOMMODATIONS TO FACILITATE THE MANUFACTURING PROCESS.	valmont Valley, NE 68064 (402) 359-2201	ORDER NUMBER: 291602-P1 PAGE NUMBER: 3 OF 5 DRAWING NUMBER: CA291602P1 REV: A
-------	---------------------------------------	--	---	--



1. FOUNDATION HOLE SHALL BE AUGERED AND FILLED WITH CONCRETE. CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH (F<sub>C</sub>) OF 3000 PSI MINIMUM AT 28 DAYS. CONCRETE SHALL HAVE A MAXIMUM SLUMP OF 4" AS DETERMINED BY ASTM C143.

2. REINFORCING STEEL SHALL BE IN ACCORDANCE WITH ASTM A615 GRADE 60 OR EQUAL.

3. GEOTECHNICAL REPORT WAS NOT MADE. FOUNDATION IS DESIGNED ASSUMING A NON-COHESIVE SOIL. SOIL HAS A POSSIBILITY OF BEING HEAVILY SENSITIVE TO MOISTURE CONTENT AND MAY HAVE POOR SHRINKAGE AND SWELLING CHARACTERISTICS. CONTRACTOR SHALL CONTACT GEOTECHNICAL ENGINEER WITH SOIL CONDITIONS.

4. IF SOIL CONDITIONS DURING CONSTRUCTION DO NOT MEET THE DESCRIPTION GIVEN ABOVE OR IF SOLID BEDROCK IS REACHED BEFORE REACHING THE SPECIFIED EMBEDMENT DEPTH CONTACT VALMONT ENGINEERING BEFORE CONTINUING EXCAVATION.

5. FOUNDATION TO BE CAST AGAINST UNDISTURBED SOIL. IF CASINGS ARE REQUIRED TO PREVENT CAVING OF THE PIER THE CASING SHALL BE PULLED AFTER USE.

6. FOUNDATION TO BE POURED MONOLITHICALLY. DUE TO THE POSSIBILITY OF EXISTING SENSITIVE SOILS THE CONCRETE SHALL BE POURED THE SAME DAY AS THE EXCAVATION.

7. FOUNDATION DESIGN IS BASED ON WATER TABLE BEING BELOW THE BOTTOM OF THE PIER. CONSTRUCTION BELOW THE WATER TABLE MAY REQUIRE SPECIAL CONSTRUCTION TECHNIQUES TO PREVENT RUPURING DUE TO HYDROSTATIC PRESSURE.

8. SITE GRADE IS 7H TO 1V OR FLATTER.

9. NO CONDUIT. LAYOUT IS SHOWN. CONDUIT BY OTHERS.

10. CONSTRUCTION SHALL BE DONE IN ACCORDANCE WITH OSHA REQUIREMENTS WITH REGARDS TO WORKER ACCESS TO THE EXCAVATION.

11. PROVIDE 3" MINIMUM CONCRETE COVER ON ALL FACES.

12. SITE REQUIREMENTS MAY ADJUST TOP OF FOOTING ABOVE GRADE. CONTRACTOR SHALL FOLLOW PROJECT REQUIREMENTS. CONTRACTOR SHALL DETERMINE TOP OF FOOTING AND ADJUST CONCRETE AND REINFORCING STEEL QUANTITIES. SITE SPECIFIC REQUIREMENTS MUST BE REVIEWED.

13. ALL MATERIALS AND CONSTRUCTION SHALL CONFORM TO THE REQUIREMENTS OF THE LATEST ACT SPECIFICATIONS. LATEST DESIGN CODES, AND LOCAL CODES.

14. CONDUIT SHALL PROJECT A MINIMUM OF 2" ABOVE THE FOUNDATION. MAXIMUM PROJECTION SHALL BE 4".

15. ALL METHODS OF CONSTRUCTION AND INSTALLATION ARE THE RESPONSIBILITY OF THE CONTRACTOR.

16. NO OTHER LOADING CONDITIONS WERE CONSIDERED AND DESIGN IS BASED ON WIND LOADS ONLY.

17. CONTRACTOR SHALL FOLLOW STATE AND LOCAL SPECIFICATIONS.

GENERAL NOTES

FOUNDATION LOADS HAVE BEEN CALCULATED BASED ON AN ASSUMED 100 MPH WIND. AN OVERTURNING (FS = 2.0) AND TORSIONAL (FS = 1.1) WERE USED IN DESIGN.

CONTRACTOR TO VERIFY NUMBER OF ANCHOR BOLTS, SIZE AND BOLT CIRCLE.

NON-COHESIVE LOOSE/MEDIUM SOIL LAYER  
 $\phi = 30^\circ$  ASSUMED  
 $\gamma = 90$  PCF ASSUMED  
 $u = 0.25$  (FRICTION FACTOR)

SOIL DATA IS BASED UPON STANDARD SOIL PARAMETERS USED. CONTRACTOR TO CONFIRM SOIL CONDITIONS ON SITE. UPPER 1'-0" PROVIDES NO PASSIVE RESISTANCE.

SOIL DATA

AXIAL = 973 LB  
 SHEAR = 1,383 LB  
 SHEAR = 0 LB  
 MOMENT = 0 FT-LB  
 MOMENT = 14,616 FT-LB  
 TORSION = 1,725 FT-LB (NOMINAL FOR DESIGN)

FOUNDATION LOADS

POLE	CAISSON DATA (EA)		LONGITUDINAL BARS (EA)		TRANSVERSE BARS (EA)	
	DIA (FT)	EMBED (FT)	NL (DIA)	SL (SIZE)	(SIZE)	
TS	2.5	7.5	8	6	#3 TIES @ 6" TOP 9.5' #3 TIES @ 12" LOWER 4"	

SPECIAL SQ TS POLES

DETAIL "B"  
 FOUNDATION DESIGN FOR  
 TRAFFIC SIGNAL STRUCTURE B


OWNER	ROLLING HILLS ESTATES DECO TRAFFIC	VALMONT INDUSTRIES, INC. RESERVES THE RIGHT TO INSTALL VARIOUS ENGINEER APPROVED, MATERIAL HANGING ACCOMMODATIONS TO FACILITATE THE MANUFACTURING PROCESS.	valmont Valley, NE 68064 (402) 359-2201	ORDER NUMBER: 291602-P1 PAGE NUMBER: 5 OF 5 DRAWING NUMBER: CA291602P1 REV: A
-------	---------------------------------------	--	---	--

FOUNDATION SIZE (S)

POLE NO.	CAISSON DATA (EA)			LONGITUDINAL BARS (EA)		TRANSVERSE BARS (EA)	
	DIA (FT)	LENGTH (FT)	CONCRETE STRENGTH (PSI)	QUANTITY	SIZE	SIZE	
30' TS POLE	2.5	9.5	4000	10	#6	#3	

GENERAL NOTES:

- REINFORCING STEEL SHALL BE IN ACCORDANCE WITH ASTM A615 GRADE 60 OR EQUAL.
- FOUNDATION TO BE CAST AGAINST UNDISTURBED SOIL.
- FOUNDATION TO BE POURED MONOLITHICALLY.
- FOUNDATION DESIGN BASED ON WATER TABLE BEING BELOW THE BOTTOM OF THE PIER. IF WATER TABLE IS ENCOUNTERED AT TIME OF EXCAVATION, CONSULT A GEOTECH ENGINEER.
- SITE GRADE IS 7H TO 1V OR FLATTER.
- ALL MATERIALS AND CONSTRUCTION SHALL CONFORM TO THE REQUIREMENTS OF THE LATEST ACI, LOCAL, AND STATE CODES.
- ALL METHODS OF CONSTRUCTION AND INSTALLATION ARE THE RESPONSIBILITY OF THE CONTRACTOR.
- DESIGN BASED ON A LOOSE SANDY SOIL USING STANDARD SOIL PARAMETERS
- ANCHOR BOLT INFORMATION CAN BE FOUND IN VALMONT CALCULATIONS DATED 09/13/2021.



OWNER	ROLLING HILLS ESTATES 30' SPCL TS POLE	VALMONT INDUSTRIES, INC. RESERVES THE RIGHT TO INSTALL VARIOUS ENGINEER APPROVED, MATERIAL HANGING ACCOMMODATIONS TO FACILITATE THE MANUFACTURING PROCESS.	valmont Valley, NE 68064 (402) 359-2201	ORDER NUMBER: 517241-P1 PAGE NUMBER: 5 OF 5 DRAWING NUMBER: CA517241P1 REV: A
-------	---	--	---	--

U:\110176 - RHE PVD\04DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\PL-SIGNAL-03.dwg Apr 03, 23 - 1:23pm

100% SUBMITTAL NOT FOR CONSTRUCTION

PLANS PREPARED BY:  
**WILLDAN Engineering** *Comprehensive Innovative Trusted*  
 13191 CROSSROADS PARKWAY NORTH  
 SUITE 405 INDUSTRY, CA 91746-3407  
 (562) 908-6200  
 UNDER THE SUPERVISION OF  
 JEFFREY LAU, RCE No. 83887 DATE

BENCH MARK: NONE

NO.	DESCRIPTION	APP.	DATE

CITY OF ROLLING HILLS ESTATES

**TRAFFIC SIGNAL FOUNDATION DETAILS**

INTERSECTION CAPACITY IMPROVEMENTS  
 AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

DRAWN BY: BR  
 DESIGNED BY: BR  
 CHECKED BY: FW

SHT. 13 OF 22 SHTS.





**SIGNING AND STRIPING GENERAL NOTES:**

1. TRAFFIC SIGNING AND STRIPING, LOOP REPLACEMENT, AND THE INSTALLATION THEREOF SHALL CONFORM TO CALTRANS REVISED STANDARD PLANS AND SPECIFICATIONS, DATED 2018, THE CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (CALIFORNIA MUTCD), LATEST EDITION, THIS PLAN AND THE SPECIAL PROVISIONS.
2. ALL STRIPING DETAILS SHALL BE PER CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (CALIFORNIA MUTCD), LATEST EDITION.
3. ALL STRIPING DETAILS AND PAVEMENT LEGENDS SHALL BE PAINT, THREE COATS, UNLESS OTHERWISE SHOWN.
4. INSTALL TWO-WAY BLUE REFLECTIVE MARKERS AT EVERY FIRE HYDRANT.
5. ALL SCHOOL SIGNS MUST BE FLUORESCENT YELLOW-GREEN (FYG).
6. SIGN POSTS FOR STREET NAME SIGNS, TRAIL SIGNS, AND MULTI-USE PATH SIGNS SHALL BE BROWN.
7. UNLESS OTHERWISE SHOWN, BIKE LANE STRIPE SHALL BE 4' FROM EDGE OF GUTTER. SEE DETAIL "C."
8. PAVEMENT MARKINGS AND TRAFFIC LINE DETAILS SHALL BE PER THE 2010 CALTRANS STANDARD PLAN DETAILS.



**SIGNING AND STRIPING CONSTRUCTION NOTES:**

- 1 PAINT STRIPING DETAIL OR PAVEMENT MARKING AS SHOWN.
- 2 PAINT 12" YELLOW CROSSWALK. CROSSWALK SHALL BE 12' IN WIDTH (INSIDE TO INSIDE) UNLESS OTHERWISE SHOWN.
- 3 PAINT 12" WHITE LIMIT LINE.
- 4 PAINT "BIKE", "LANE" AND BIKE LANE ARROW PAVEMENT LEGEND.
- 5 REMOVE CONFLICTING STRIPING BY WET SANDBLASTING, INCLUDING RAISED PAVEMENT MARKINGS.
- 6 PAINT MEDIAN NOSE CURB WITH YELLOW REFLECTIVE CURB PAINT PER DETAIL "B."
- 7 INSTALL SIGN AND POST AS SHOWN.
- 8 INSTALL SIGN AND POST AS SHOWN PER DETAIL "B."
- 9 REMOVE SIGN AND POST AS SHOWN.
- 10 RELOCATE SIGN AND POST AS SHOWN.
- 11 RELOCATE SIGN ON NEW POST AS SHOWN.




**NOTES:**

- 1 INSTALL HIGH REFLECTIVITY PAINT TO MATCH EXISTING COLOR ON CURB FACE. EXTEND PAINT ON TOP OF CURB AND CURB FACE TO BC, EC, OR END OF FLARE.
- 2 EPOXY
- 3 SERIES 400 REPO POST.(18")
- 4 TYPE K MARKER.



U:\110176 - RHE PVND@DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\PL-STRIPPE-01.dwg Apr 03, 23 - 1:23pm

100% SUBMITTAL NOT FOR CONSTRUCTION



PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
 13191 CROSSROADS PARKWAY NORTH  
 SUITE 405 INDUSTRY, CA 91746-3497  
 (562) 908-6200  
 UNDER THE SUPERVISION OF  
 JEFFREY LAU, RCE No. 83887 DATE

BENCH MARK:  
 NO. \_\_\_\_\_ ELEV. \_\_\_\_\_  
 DATE ADJ. \_\_\_\_\_ QUAD. \_\_\_\_\_  
 NONE

REVISIONS		
NO.	DESCRIPTION	APP. DATE


**CITY OF ROLLING HILLS ESTATES**

**SIGNING AND STRIPING PLAN**

INTERSECTION CAPACITY IMPROVEMENTS  
 AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE


DRAWN BY: RG/KC  
 DESIGNED BY: RG/KC  
 CHECKED BY: JL

SHT. 14 OF 22 SHTS.




**IRRIGATION CONSTRUCTION NOTES:**


1. **P.O.C. - WATER CONNECTION TO EXISTING WATER METER**  
 CONTRACTOR SHALL COORDINATE WITH THE WATER UTILITY/SUPPLIER AGENCY AND WITH ENGINEER FOR THE CONNECTION (DOWNSTREAM) TO THE EXISTING WATER SERVICE METER. FIELD LOCATE AND VERIFY EXISTING WATER METER SIZE AND CONDITION WITH THE UTILITY AGENCY'S REPRESENTATIVE AND ENGINEER PRIOR TO CONNECTION. COORDINATE WITH CIVIL ENGINEERING STREET IMPROVEMENT PLAN FOR ANY ADDITIONAL TASK THAT MAY NEED TO BE PERFORMED TO THE EXISTING WATER METER PRIOR TO CONNECTION.  
 BACKFLOW DEVICE AND RELATED EQUIPMENT AS SPECIFIED ON THE PLAN SHALL BE LOCATED IN MEDIAN PLANTING AREA. VERIFY EXACT LOCATION OF BACKFLOW DEVICE AND RELATED EQUIPMENT AS SHOWN ON PLAN WITH ENGINEER AND UTILITY AGENCY'S REPRESENTATIVE PRIOR TO INSTALLATION.  
 CONTACT: CITY OF ROLLING HILLS ESTATE, DEPT. OF PUBLIC WORKS  
 (310)377-1577 ext. 103  
 CALIFORNIA WATER SERVICES - RANCHO DOMINGUEZ DISTRICT  
 (310)257-1400
2. **EXISTING BACKFLOW PREVENTER DEVICE**  
 TO ACCOMMODATE RETAINING WALL CONSTRUCTION, CONTRACTOR SHALL REMOVE, SALVAGE AND RETURN EXISTING BACKFLOW PREVENTER DEVICE TO THE CITY DEPT. OF PUBLIC WORKS. CUT AND CAP ALL SUPPLY WATER LINES CONNECTED TO EXISTING WATER METER.
3. **NEW IRRIGATION CONTROLLER**  
 INSTALL NEW IRRIGATION CONTROLLER (PER LEGEND) AT THIS LOCATION IN MEDIAN PLANTING AREA. VERIFY EXACT LOCATION WITH ENGINEER PRIOR TO INSTALLATION. INSTALL PULL BOX FOR CONTROLLER WIRE SPLICES PRIOR FOR WIRES TO ENTERING CONTROLLER ASSEMBLY.



MATCH LINE  
SEE LOWER LEFT



MATCH LINE  
SEE UPPER RIGHT




**CITY OF ROLLING HILLS ESTATES**  
**STREET MEDIAN & PARKWAY**  
**IRRIGATION PLAN**

INTERSECTION CAPACITY IMPROVEMENTS  
 AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE



DRAWN BY: BN  
 DESIGNED BY: BN  
 CHECKED BY: JH

SHT. 16 OF 22 SHTS.  
 PLAN NO. **L-2**



PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
 13191 CROSSROADS PARKWAY NORTH  
 SUITE 405 INDUSTRY, CA 91746-3497  
 (562) 908-6200  
 UNDER THE SUPERVISION OF  
 JOHN HIDALGO R.L.A. 3551 DATE

BENCH MARK:		NO.		REVISIONS	
NO.	ELEV.	NO.	DESCRIPTION	APP.	DATE
DATE ADJ.	QUAD.				
NONE					






**CONSTRUCTION NOTES:**

- ① CONSTRUCT COBBLESTONE PAVING. SEE DETAIL 5, PLAN NO. L-8.
- ② SEE TYPICAL CROSS SECTION, SEE DETAIL 6, PLAN NO. L-8.
- ③ CONSTRUCT BUS SHELTER. SEE DETAILS, PLAN NO. L-5 & L-6.
- ④ FURNISH AND INSTALL PVC VINYL RAIL FENCE. SEE DETAIL 7, PLAN NO. L-8.

**DEMOLITION/REMOVAL NOTES:**

- A REMOVE AND PROPERLY DISPOSE EXISTING TREE, COMPLETE INCLUDING ROOTS TO 24" DEPTH.
- B EXISTING TREE TO BE REMOVED AS PART OF THE CIVIL IMPROVEMENT AND CONSTRUCTION PLAN.
- C EXISTING BUS SHELTER TO BE REMOVED AND PROPERLY DISPOSED AS PART OF THE CIVIL IMPROVEMENT AND CONSTRUCTION PLAN. COORDINATE WITH CIVIL STREET IMPROVEMENT PLAN FOR ADDITIONAL DIRECTIONS FOR TREES AND BUS SHELTER REMOVAL.



**GENERAL CONSTRUCTION NOTES:**

- 1. VERIFY EXACT LOCATION OF NEW BUS SHELTER WITH ENGINEER PRIOR TO CONSTRUCTION.
- 2. VERIFY EXACT LOCATION OF PVC VINYL RAIL FENCE WITH ENGINEER PRIOR TO INSTALLATION.
- 3. VERIFY ALL LOCATIONS AND QUANTITY OF EXISTING TREES INDICATED "TO BE REMOVED" WITH ENGINEER PRIOR TO REMOVAL.

ABBREVIATIONS:  
 CF CURB FACE  
 EQ. EQUAL  
 PA PLANTING AREA  
 RL REF. LINE  
 WT WALL TERMINUS  
 TYP. TYPICAL



PLANS PREPARED BY:  
**WILLDAN Engineering** *Comprehensive Innovative Trusted*  
 13191 CROSSROADS PARKWAY NORTH  
 SUITE 405 INDUSTRY, CA 91746-3497  
 (562) 908-6200  
 UNDER THE SUPERVISION OF  
 JOHN HIDALGO R.L.A. 3551 DATE

BENCH MARK:  
 NO. \_\_\_\_\_ ELEV. \_\_\_\_\_  
 DATE ADJ. \_\_\_\_\_ QUAD. \_\_\_\_\_  
 NONE

REVISIONS		
NO.	DESCRIPTION	APP. DATE

**CITY OF ROLLING HILLS ESTATES**  
**STREET MEDIAN & PARKWAY LANDSCAPE CONSTRUCTION PLAN**

INTERSECTION CAPACITY IMPROVEMENTS  
 AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE





DRAWN BY: BN  
 DESIGNED BY: BN  
 CHECKED BY: JH  
 PLAN NO. L-1  
 SHT. 15 OF 22 SHTS.

U:\110176 - RHE PVDN@DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\Landscape Dwgs\L-CONST-01.dwg Apr 03, 23 - 1:23pm

100% SUBMITTAL NOT FOR CONSTRUCTION







**PLANTING LEGEND**

**TREES**

SYM	BOTANICAL NAME	COMMON NAME	SIZE	QTY	REMARKS	DET.	SHT.	HT. SP.	WUCOLS
	CERCIS OCCIDENTALIS	WESTERN RED BUD	24 GAL.	4	STANDARD	1 & 2	L-8	20' 15'-20'	L
	SCHINUS MOLLE	CALIFORNIA PEPPER	24 GAL.	9	STANDARD	1 & 2	L-8	25'-50' 25'-40'	L

**SHRUBS**

SYM	BOTANICAL NAME	COMMON NAME	SIZE	QTY	REMARKS	DET.	SHT.	HT. SP.	WUCOLS
	AGAVE DESMETTIANA	SMOOTH AGAVE	5 GAL.	54	SPACING PER PLAN	3	L-8	3' 3'	L
	SALVIA LEUCANTHA 'SANTA BARBARA'	SANTA BARBARA SAGE	5 GAL.	67	SPACING PER PLAN	3		3' 3'	L
	MUHLENBERGIA CAPILLARIS 'REGAL MIST'	PINK MUHLY	5 GAL.	54	SPACING PER PLAN	3		3' 3'	L

**GROUNDCOVERS**

	ARTOSTRAPHYLUS UVA-URSI 'POINT REYES'	BEARBERRY	1 GAL.	148	SPACING @ 36" O.C.	3	L-8	12" 15'	L
--	---------------------------------------	-----------	--------	-----	--------------------	---	-----	------------	---

WUCOLS: WATER USE CLASSIFICATIONS OF LANDSCAPE SPECIES  
H: HIGH M: MODERATE L: LOW

**PLANTING NOTES:**

- VERIFY EXACT TREE LOCATIONS WITH ENGINEER PRIOR TO INSTALLATION.
- CONTRACTOR SHALL CHALK LAYOUT SHRUB MASSES AND GROUNDCOVERS WITHIN THE PLANTING AREAS AND VERIFY WITH ENGINEER PRIOR TO INSTALLATION.
- CONTRACTOR SHALL FURNISH AND INSTALL 3-INCH LAYER OF SHREDDED REDWOOD CHIPS, LARGE GRIND, AS TOP DRESS IN ALL SHRUB & GROUNDCOVER AREAS. REDWOOD CHIPS AVAILABLE THROUGH RECYCLED WOOD PRODUCTS. (877)GROW RWP hank@wpmulch.com
- ALL PLANTING BACKFILL AMENDMENTS SHALL BE SUPPLEMENTED WITH "TRI-C HUMATE PLUS" & "MYCO PAK" MANUFACTURED BY TRI-C (909) 590-1790 <https://www.tri-corganics.com/> BACKFILL MIXTURE SHALL FOLLOW MANUFACTURER'S SPECIFICATIONS.
- KEEP REDWOOD CHIPS 6 INCHES CLEAR FROM SHRUB STEM.
- QUANTITIES SHOWN ON LEGEND ARE FOR CONVENIENCE ONLY, CONTRACTOR SHALL VERIFY EXACT QUANTITY OF EACH SHRUB & GROUNDCOVER SPECIES WITH ENGINEER PRIOR TO COMMENCING PLANTING.

**TREES, SHRUBS AND GROUNDCOVER PROCUREMENT**

CONTRACTOR SHALL BE RESPONSIBLE FOR CONTRACT GROW, AT THE CONTRACTOR'S EXPENSE, ALL THE PLANTS LISTED ON THE PLANTING LEGEND. CONTRACTOR SHALL PROVIDE TO THE CITY AN INVOICE OF ALL THE LISTED PLANTS THAT WILL BE CONTRACT GROWN AND/OR RESERVED. THE PROCUREMENT INVOICE STATEMENT SHALL BE SUBMITTED TO THE CITY ENGINEER FOR REVIEW AND APPROVAL WITHIN 15 DAYS OF AWARD OF CONTRACT.

TREES & SHRUBS AVAILABLE THROUGH LANDSCAPE RESOURCE INC. (760)798-9810 [aj@landscaperesourcesinc.com](mailto:aj@landscaperesourcesinc.com), [Tvega722@gmail.com](mailto:Tvega722@gmail.com)

**PLANTING CONSTRUCTION NOTE:**

- FURNISH AND INSTALL ROOT CONTROL BARRIER. SEE DETAIL 1, PLAN NO L-8.
- FURNISH AND INSTALL 3" LAYER OF REDWOOD CHIPS PER GENERAL NOTE NO. 3.

**CITY OF ROLLING HILLS ESTATES**

**STREET MEDIAN & PARKWAY PLANTING PLAN**


INTERSECTION CAPACITY IMPROVEMENTS  
AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

DRAWN BY: BN  
DESIGNED BY: BN  
CHECKED BY: JH

PLAN NO.

L-4

SHT. 18 OF 22 SHTS.



PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
13191 CROSSROADS PARKWAY NORTH  
SUITE 405 INDUSTRY, CA 91746-3497  
(562) 908-6200  
UNDER THE SUPERVISION OF  
JOHN HIDALGO R.L.A. 3551 DATE

**BENCH MARK:**


NO. \_\_\_\_\_ ELEV. \_\_\_\_\_  
DATE ADJ. \_\_\_\_\_ QUAD. \_\_\_\_\_

NONE

**REVISIONS**

NO.	DESCRIPTION	APP.	DATE





LOCATION 1

GENERAL NOTES:

1. VERIFY EXACT LOCATION OF BUS SHELTER, BENCH AND TRASH RECEPTACLE WITH ENGINEER PRIOR TO CONSTRUCTION AND INSTALLATION.
2. DETAILS AND PLANS SHOWN ARE TO ILLUSTRATE THE DESIGN INTENT ONLY. THE CONTRACTOR SHALL SUBMIT COMPLETE SHOP DRAWINGS AND CONSTRUCTION MATERIAL SUBMITTALS TO ENGINEER FOR APPROVAL PRIOR TO CONSTRUCTION.
3. SHOP DRAWING SHALL INCLUDE ALL SPECIFICATION CALL-OUTS AND DIMENSIONS AS SHOWN INCLUDING ANY NEEDED DIMENSIONS AND CALL-OUTS NOT SHOWN. CONTRACTOR SHALL BE RESPONSIBLE FOR SUBMITTING FOOTING CALCULATIONS FROM A CALIFORNIA REGISTERED ENGINEER TO THE CITY AS PART OF THE BUILDING PERMIT PLAN CHECK SUBMITTAL FOR REVIEW AND APPROVAL.
4. BUS SHELTER COLOR SCHEDULE, BUILDING MATERIAL, AND SITE FURNISHING COLOR SHALL BE AS INDICATED ON THE DRAWINGS.
5. CONTRACTOR SHALL COORDINATE VERIFY ALL EXISTING UTILITY STRUCTURES WITH CIVIL IMPROVEMENT PLANS WITHIN AND SURROUNDING THE PROPOSED BUS SHELTER LOCATIONS AS SHOWN ON PLAN WITH ENGINEER PRIOR TO INSTALLATION.

CONTRACTOR'S RESPONSIBILITIES:

1. CONSTRUCT BUS SHELTER, FURNISH AND INSTALL SOLAR POWERED LIGHTING ASSEMBLY, FURNISH AND INSTALL SITE FURNISHING, COMPLETE PER PLAN.
2. CONTRACTOR SHALL COORDINATE WITH MANUFACTURERS TO OBTAIN SHOP DRAWINGS OF BUS BENCH, TRASH RECEPTACLE, SOLAR LIGHT ASSEMBLY AND CUT SHEETS/SAMPLES OF ROOFING MATERIAL AND STONE VENEER FOR CITY REVIEW SUBMITTAL, INCLUDING SHIPPING AND DELIVERY SCHEDULING PRIOR TO PLACING ORDER.
3. CONTRACTOR SHALL FURNISH SHOP DRAWINGS OF A COMPLETE BUS SHELTER ASSEMBLY PER GENERAL NOTE NO. 2 & 3 TO THE ENGINEER FOR REVIEW AND APPROVAL PRIOR TO CONSTRUCTION.
4. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY CITY BUILDING PERMIT APPLICATION, STRUCTURAL PLAN CHECK SUBMITTAL AND FEE, IF REQUIRED, FOR THE INSTALLATION OF SHELTER.
5. CONTRACTOR SHALL VERIFY EXACT COLORS OF TRASH RECEPTACLE AND BENCH WITH THE CITY PRIOR TO ORDERING.
6. CONTRACTOR SHALL:
  - FURNISH ALL NEEDED GALVANIZED STEEL HARDWARE THAT WAS NOT PROVIDED BY THE MANUFACTURERS FOR THE ANCHORING OF BENCH, TRASH RECEPTACLE AND SOLAR POWERED LIGHTING ASSEMBLY AT LOCATIONS SHOWN ON PLAN. ALL INSTALLATION AND ANCHORING SHALL FOLLOW MANUFACTURER'S SPECIFICATIONS/INSTRUCTIONS.
  - APPLY CLEAR ANTI-GRAFFITI COATING ON ALL EXPOSED SURFACES OF SHELTER. ANTI-GRAFFITI COATING SHALL BE PER SPECIFICATIONS. COATING APPLICATION SHALL BE PER MANUFACTURER'S SPECIFICATIONS/Written INSTRUCTIONS.
  - ALL INSTALLATION AND SITE FURNISHING ANCHORING SHALL FOLLOW MANUFACTURER'S SPECIFICATIONS/INSTRUCTIONS.

LUMBER NOTE: ALL WOOD TO BE ROUGH SAWN DOUGLAS FIR (D.F.) NO.1 GRADE OR BETTER.


PAINT NOTE:

- PRIME AND PAINT ALL EXTERIOR SURFACE OF WOOD MEMBERS AND METAL HARDWARE(a) WITH 1 COAT PRIMER, 2 COATS ENAMEL COLOR: WARM WHITE-DEW380 BY DUNN-EDWARDS CO.
- PROVIDE CITY ENGINEER W/ COLOR SAMPLE PRIOR TO CONSTRUCTION. SEE SPECIFICATIONS FOR ADDITIONAL INFORMATION.


(a) FOR GALV. STEEL HARDWARE, USE ULGMOO AS PRIMER.

MANUFACTURER CONTACTS:

- \* SOLAR POWERED SHELTER LIGHTING ASSEMBLY URBAN SOLAR (503)356-5516 info@urbansolarcorp.com
- \*\* BENCH AND TRASH RECEPTACLE DUMOR (800)598-4018 sales@dumor.com
- EAGLE ROOFING PRODUCT (800)300-3245 www.eagleroofting.com
- DUNN EDWARDS CONTACT: DAVE MAJOR (310)909-3769 dave.major@dunndwards.com




LOCATION 2



TYPICAL CROSS SECTION A-A NTS

NOTES:

1. APPLY NON-GLOSS CONCRETE SEALER COATING ON PCC PAD MANUFACTURED BY DAVIS COLORS OR APPROVED EQUAL. APPLICATION SHALL BE PER MANUFACTURER'S INSTRUCTIONS.
2. SUBMIT CUT SHEET OF CONCRETE SEALER TO ENGINEER FOR REVIEW AND APPROVAL PRIOR TO APPLICATION.
3. CONTRACTOR SHALL SUBMIT 2'x2' MOCKED-UP SAMPLE OF TOP-CAST FINISH PCC PAVING TO ENGINEER FOR REVIEW AND APPROVAL PRIOR TO CONSTRUCTION.



GENERAL NOTE:

TOP DRESS SEALANT WITH SILICA SAND. SEALANT COLOR TO MATCH ADJACENT CONCRETE COLOR.

CITY OF ROLLING HILLS ESTATES


BUS SHELTER LAYOUT AND CONSTRUCTION NOTES

INTERSECTION CAPACITY IMPROVEMENTS AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

DRAWN BY: BN  
DESIGNED BY: BN  
CHECKED BY: JH

PLAN NO.  
L-6

SHT. 20 OF 22 SHTS.



PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
13191 CROSSROADS PARKWAY NORTH  
SUITE 405 INDUSTRY, CA 91746-3497  
(862) 908-6200  
UNDER THE SUPERVISION OF  
JOHN HIDALGO R.L.A. 3551 DATE

BENCH MARK:



NO. \_\_\_\_\_ ELEV. \_\_\_\_\_  
DATE ADJ. \_\_\_\_\_ QUAD. \_\_\_\_\_

NONE

REVISIONS			
NO.	DESCRIPTION	APP.	DATE



- 1 LEIT X SERIES IRRIGATION CONTROLLER\*
- 2 MOUNTING COLUMN
- 3 SUB-GRADE
- 4 FINISHED GRADE / SURFACE
- 5 DIRECT BURIAL CONTROL WIRES TO CONTROL VALVES
- 6 90° SWEEP ELL
- 7 TERMINAL STRIP
- 8 12" DIA. X 18" CONCRETE FOOTING
- 9 ACCESS KEY
- 10 RAIN SENSOR INSTALLED IN STAINLESS STEEL VANDAL-PROOF ENCLOSURE MOUNTED ON IRRIGATION CONTROLLER ENCLOSURE. INSTALLATION SHALL BE PER MANUFACTURER'S SPECIFICATIONS
- 11 STAINLESS STEEL ENCLOSURE
- 12 PADLOCK FURNISH AND PROVIDE TO CITY'S REPRESENTATIVE (2) KEYS FOR PADLOCK @ EACH CONTROLLER
- 13 FINISH GRADE

\*ASSEMBLY INCLUDES:  
 1. LEIT X SERIES IRRIGATION CONTROLLER\*  
 2. MOUNTING COLUMN - MC0XLX  
 3. STAINLESS STEEL ENCL - ENCL4000  
 4. SENSOR ADAPTER - SKIT 8821-4



- NOTES:  
 1. ALL FITTINGS AND RISERS TO BE RED BRASS.  
 2. PCC PAD SIZE SHALL BE SUFFICIENT TO ACCOMMODATE BACKFLOW PREVENTER ENCLOSURE.  
 3. INSTALL WY STRAINER-PRESSURE REGULATOR IN SEPARATE VALVE BOX.  
 4. VERIFY EXACT LOCATION WITH ENGINEER PRIOR TO INSTALLATION.  
 5. INSTALL BACKFLOW PREVENTER AS REQUIRED BY LOCAL CODES AND HEALTH DEPARTMENT. VERIFY LOCAL REQUIREMENTS PRIOR TO INSTALLATION.







NOTE:  
 REFER TO MANUFACTURER'S GUIDELINES AND SPECIFICATIONS FOR ADDITIONAL INFORMATION.








- 1 FILTER FABRIC
- 2 RECT. PLASTIC VALVE BOX W/ BOLT-DOWN COVER, ETCH "WS" ON LID. SIZE TO FIT
- 3 FINISHED GRADE
- 4 UNION (2 REQ') SCH. 80 PVC
- 5 WYE STRAINER
- 6 VALVE BOX EXTENSION AS NEEDED
- 7 PRESSURE MAINLINE
- 8 COMMON BRICK (4 REQ')
- 9 2 CU. FT. PEA GRAVEL

NOTE:  
 SET PRESSURE REGULATOR +5 PSI ABOVE MIN. PRESSURE REQUIRED.




**1 IRRIGATION CONTROLLER ASSEMBLY NTS 2 BACKFLOW PREVENTER DEVICE NTS 3 MASTER VALVE NTS 4 WYE STRAINER /PRESSURE REGULATOR NTS**





**5 GATE VALVE NTS 6 QUICK COUPLER VALVE NTS 7 CONTROL WIRE SPLICE BOX NTS 8 TRENCHING UNDER ROADWAY NTS 9 TRENCHING IN PLANTING AREA NTS 10 BORING UNDER ROADWAY NTS**



**11 DRIP ZONE CONTROL KIT NTS 12 TYPICAL DRIP IRRIGATION LAYOUT NTS 13 OPERATION INDICATOR NTS 14 LINE FLUSHING VALVE NTS**



**15 RZWS NTS 16 REMOTE CONTROL VALVE NTS**



U:\110176 - RHE PVD\DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\Landscape Dwg\1-LNSPC DETAILS.dwg Apr 03, 23 - 1:25pm

100% SUBMITTAL NOT FOR CONSTRUCTION



PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
 13191 CROSSROADS PARKWAY NORTH  
 SUITE 405 INDUSTRIAL, CA 91746-3497  
 (862) 908-6200  
 UNDER THE SUPERVISION OF  
 JOHN HIDALGO R.L.A. 3551 DATE

BENCH MARK:	NONE		
NO. _____ ELEV. _____			
DATE ADJ. _____ QUAD. _____			
	REVISIONS		
	NO. DESCRIPTION	APP.	DATE

**CITY OF ROLLING HILLS ESTATES**




**IRRIGATION DETAILS**

INTERSECTION CAPACITY IMPROVEMENTS  
 AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

DRAWN BY: BN	SHT. 21 OF 22 SHTS.	PLAN NO.
DESIGNED BY: BN		<b>L-7</b>
CHECKED BY: JH		

**NOTES**  
 THIS DETAIL IS FOR INSTALLATION OF ROOT BARRIER. REFER TO TREE INSTALLATION DETAILS FOR TREE INSTALLATION.

**ROOT BARRIER NOTES**  
 1. TOP OF ROOT CONTROL BARRIER MUST BE AT GRADE.  
 2. POSITION ROOT CONTROL BARRIER ADJACENT TO STRUCTURE.  
 3. RAISED ROOT DEFLECTORS MUST BE FACING PLANTED AREA.  
 4. PROVIDE A MIN. OF 12 FEET OF ROOT BARRIER PER TREE.  
 5. ROOT BARRIER SHALL BE A MIN. OF 24" BELOW GRADE.  
 6. ROOT BARRIER SHALL BE MANUFACTURED BY "NDS" OR "DEEP ROOT".




1 ROOT CONTROL BARRIER NTS


2 TREE PLANTING NTS

3 SHRUB & GROUND COVER PLANTING NTS


4 NOT USED NTS



5 COBBLESTONE PAVING NTS



6 TYPICAL MEDIAN CROSS SECTION NTS




7 PVC VINYL RAIL FENCE NTS

8 NOT USED NTS

U:\110176 - RHE PVDN@DAPPLEGRAY ELM SCHOOL\900-PS&E\901-Plans\Landscape Dwgs\L-LNSCP DETAILS.dwg Apr 03, 23 - 1:25pm

100% SUBMITTAL NOT FOR CONSTRUCTION



PLANS PREPARED BY:  
**WILLDAN Engineering** Comprehensive Innovative Trusted  
 13191 CROSSROADS PARKWAY NORTH  
 SUITE 405 INDUSTRY, CA 91746-3497  
 (562) 908-6200  
 UNDER THE SUPERVISION OF  
 JOHN HIDALGO R.L.A. 3551 DATE

BENCH MARK:  
 NO. \_\_\_\_\_ ELEV. \_\_\_\_\_  
 DATE ADJ. \_\_\_\_\_ QUAD. \_\_\_\_\_  
 NONE

REVISIONS		
NO.	DESCRIPTION	APP. DATE

**CITY OF ROLLING HILLS ESTATES**

**LANDSCAPE CONSTRUCTION DETAILS**

INTERSECTION CAPACITY IMPROVEMENTS  
 AT PALOS VERDES DRIVE NORTH AND DAPPLEGRAY SCHOOL ENTRANCE

DRAWN BY: BN	PLAN NO.
DESIGNED BY: BN	SHT. 22 OF 22 SHTS.
CHECKED BY: JH	<b>L-8</b>